

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

PLT 2 BLACK 980

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Pad printing ink

#### **Identified Uses**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8a	Transfer of substance or mixture (charging and discharging) at nondedicated facilities
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring
PROC19	Manual activities involving hand contact
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8d	Wide dispersive outdoor use of processing aids in open systems

#### **Uses advised against**

SU21 Consumer uses: Private households (= general public = consumers)

### **1.3. Details of the supplier of the safety data sheet**

#### **Address/Manufacturer**

COMEC ITALIA SRL  
 Piazzale del lavoro 149  
 21044 Cavarina (VA)  
 ITALIA  
 Tel. +39 0331 219516  
 Fax +39 0331 216161

E-mail address of person responsible for this SDS

info@comec-italia.it  
 Edgardo Baggini

### **1.4. Emergency telephone number**

CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h) - CENTRO ANTIVELENI POLICLINICO A.GEMELL ROMA Tel. 06/3054343 (24/24h) -

## **SECTION 2: Hazards identification \*\*\***

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H335
STOT SE 3	H336
Aquatic Chronic 3	H412

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard pictograms \*\*\*



##### Signal word

Danger

##### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261.9	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.

##### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains	Solvent naphtha (petroleum), light arom. Cyclohexanone; 2-Methoxy-1-methylethyl acetate
EUH208 Contains	Phthalic anhydride, May produce an allergic reaction.

### 2.3. Other hazards

No special hazards have to be mentioned.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Pad printing ink based on polyester resins and on solvents

#### Hazardous ingredients

##### Solvent naphtha (petroleum), light arom.

CAS No. 64742-95-6

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

EINECS no. 265-199-0  
Registration no. 01-2119455851-35 (LIST NUMBER 918-668-5)  
Concentration >= 20 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226  
STOT SE 3 H336  
STOT SE 3 H335  
Asp. Tox. 1 H304  
Aquatic Chronic 2 H411

### Cyclohexanone

CAS No. 108-94-1  
EINECS no. 203-631-1  
Registration no. 01-2119453616-35  
Concentration >= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H332  
Flam. Liq. 3 H226  
Acute Tox. 4 H302  
Acute Tox. 4 H312  
Eye Dam. 1 H318  
Skin Irrit. 2 H315

### 2-Methoxy-1-methylethyl acetate

CAS No. 108-65-6  
EINECS no. 203-603-9  
Registration no. 01-2119475791-29  
Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226  
STOT SE 3 H336

### Phthalic anhydride

CAS No. 85-44-9  
EINECS no. 201-607-5  
Concentration >= 0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2 H315  
Skin Sens. 1 H317  
Eye Dam. 1 H318  
STOT SE 3 H335  
Acute Tox. 4 H302  
Resp. Sens. 1 H334

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

## 4.3. Indication of any immediate medical attention and special treatment needed

### Hints for the physician / treatment

Treat symptomatically

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist, Not be used for safety reasons: water jet

### 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO); dense black smoke; Hydrogen chloride (HCl)

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### 6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

## SECTION 7: Handling and storage

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

#### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T2

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3. Specific end use(s)

Pad printing ink

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### 2-Methoxy-1-methylethyl acetate

List	EH40		
Type	WEL		
Value	274	mg/m <sup>3</sup>	50 ppm(V)
Short term exposure limit	548	mg/m <sup>3</sup>	100 ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011			

##### Cyclohexanone

List	EH40		
Type	WEL		
Value			10 ppm(V)
Short term exposure limit			20 ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2005			

##### Mesitylene

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)
Status:	2011			

**1,2,4-Trimethylbenzene**

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)
Status:	2011			

**Phthalic anhydride**

List	EH40			
Type	WEL			
Value	4	mg/m <sup>3</sup>		
Short term exposure limit	12	mg/m <sup>3</sup>		
Status:	2011			

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**2-Methoxy-1-methylethyl acetate**

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	dermal			
Mode of action	Systemic effects			
Concentration	796			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	inhalative			
Mode of action	Systemic effects			
Concentration	275			mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	dermal			
Mode of action	Systemic effects			
Concentration	320			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	inhalative			
Mode of action	Systemic effects			
Concentration	33			mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	inhalative			
Mode of action	Local effects			
Concentration	33			mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	oral			

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Mode of action	Systemic effects	
Concentration	36	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Lifetime	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	550	mg/m <sup>3</sup>

**Solvent naphtha (petroleum), light arom.**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d

**Cyclohexanone**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	40	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	80	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	40	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	80	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	10	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	20	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	20	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Concentration	40	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	1	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	1	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1,5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1,5	mg/kg/d
<b>Phthalic anhydride</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,2	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	10	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	8,6	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Concentration	5	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	5	mg/kg

**Predicted No Effect Concentration (PNEC)**

**2-Methoxy-1-methylethyl acetate**

Reference substance	2-Methoxy-1-methylethyl acetate	
Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	3,29	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l
Source	Literature value	
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,329	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

**Cyclohexanone**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,033	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,003	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,249	mg/kg
Type of value	PNEC	

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Type	Marine sediment	
Concentration	0,025	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,03	mg/kg
<b>Phthalic anhydride</b>		
Type of value	PNEC	
Type	Freshwater	
Concentration	1	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,1	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	5,6	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Sediment	
Concentration	3,8	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,38	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,173	mg/kg

**8.2. Exposure controls****Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

**Eye protection**

Use safety eyewear designed to protect against splash of liquids.

**Body protection**

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Form</b>	Pasty		
<b>Colour</b>	coloured		
<b>Odour</b>	solvent-like		
<b>Odour threshold</b>			
Remarks	No data available		
<b>pH value</b>			
Remarks	Not applicable		
<b>Melting point</b>			
Remarks	not determined		
<b>Freezing point</b>			
Remarks	not determined		
<b>Initial boiling point and boiling range</b>			
Value	appr. 148		°C
Pressure	1.013	hPa	
Source	Literature value		
<b>Flash point</b>			
Value	45		°C
Method	ASTM D 6450 (CCCFP)		
<b>Evaporation rate (ether = 1) :</b>			
Remarks	not determined		
<b>Flammability (solid, gas)</b>			
Not applicable			
<b>Upper/lower flammability or explosive limits</b>			
Lower explosion limit	appr. 0,7		%(V)
Upper explosion limit	appr. 10,8		%(V)
Source	Literature value		
<b>Vapour pressure</b>			
Value	appr. 4		hPa
Temperature	20	°C	
Method	calculated		
<b>Vapour density</b>			
Remarks	not determined		
<b>Density</b>			
Value	1,04		g/cm <sup>3</sup>
Temperature	20	°C	
Method	DIN EN ISO 2811		
<b>Solubility in water</b>			

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

Remarks partially miscible

### Partition coefficient: n-octanol/water

Remarks Not applicable

### Ignition temperature

Value appr. 315 °C

Source Literature value

### Efflux time

Value > 150 s

Method DIN 53211 4 mm

### Explosive properties

evaluation no

### Oxidising properties

evaluation None known

## 9.2. Other information

### Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

### 10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity

ATE > 2.000 mg/kg  
Method calculated value (Regulation (EC) No. 1272/2008)

#### Acute oral toxicity (Components)

##### Cyclohexanone

Species rat  
LD50 1620 mg/kg

#### Acute dermal toxicity

ATE > 2.000 mg/kg  
Method calculated value (Regulation (EC) No. 1272/2008)

#### Acute inhalational toxicity

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

ATE	> 20	mg/l
Administration/Form	Vapors	
Method	calculated value (Regulation (EC) No. 1272/2008)	
ATE	> 5	mg/l
Administration/Form	Dust/Mist	
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

**Acute inhalative toxicity (Components)****Cyclohexanone**

Species	rat	
LC50	> 6,2	mg/l
Duration of exposure	4	h
Administration/Form	Vapors	

**Skin corrosion/irritation**

evaluation	irritant
Remarks	The classification criteria are met.

**Skin corrosion/irritation (Components)****2-Methoxy-1-methylethyl acetate**

Species	rabbit
evaluation	non-irritant

**Serious eye damage/irritation**

evaluation	corrosive
Remarks	The classification criteria are met.

**Sensitization**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Mutagenicity**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Reproductive toxicity**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Carcinogenicity**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Specific Target Organ Toxicity (STOT)****Single exposure**

Remarks	The classification criteria are met.
evaluation	May cause respiratory irritation.
evaluation	May cause drowsiness or dizziness.

**Repeated exposure**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Aspiration hazard**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Irritating to skin. The liquid splashed in the eyes may cause irritation. Causes serious eye damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### Fish toxicity (Components)

##### Solvent naphtha (petroleum), light arom.

Species	rainbow trout ( <i>Oncorhynchus mykiss</i> )	
LL50	9,2	mg/l
Duration of exposure	96	h

##### Cyclohexanone

Species	Fathead minnow ( <i>Pimephales promelas</i> )	
LC50	630000	µg/l

#### Daphnia toxicity (Components)

##### Solvent naphtha (petroleum), light arom.

LL0	3,2	mg/l
Duration of exposure	48	h

#### Algae toxicity (Components)

##### Solvent naphtha (petroleum), light arom.

Species	Desmodesmus	
ErC50	0,42	mg/l
Duration of exposure	72	h

##### Solvent naphtha (petroleum), light arom.

Species	Pseudokirchneriella subcapitata	
EC50	0,29	mg/l
Duration of exposure	72	h
Source	REACH registration dossier	

### 12.2. Persistence and degradability

#### General information

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

#### General information

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

### 12.4. Mobility in soil

#### General information

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

#### General information

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

There are no data available on the mixture itself.

**12.6. Other adverse effects**

**General information**

There are no data available on the mixture itself.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12\* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

**Disposal recommendations for packaging**

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

**SECTION 14: Transport information**

**Safety data sheet in accordance with regulation (EC) No 1907/2006**

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Remarks	The product is viscous; non-dangerous good in Containers with not more than 450 ltrs.	Transport according to 2.3.2.5 of the IMDG Code	
Limited Quantity	5 l		
Transport category	3		
14.5. Environmental hazards	-	no	-

**Information for all modes of transport**

**14.6. Special precautions for user**

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

no

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Major-accident categories acc. 96/82/EC**

Category 6 Flammable 5.000.000 kg 50.000.000 kg

**VOC**

VOC (EU) 55,8 %  
 VOC (EU) 580,3 g/l

**Other information**

All components are contained in the PICCS inventory.

All components are contained in the DSL inventory.

## Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 2 BLACK 980

Version: 11 / GB

Date revised: 17.06.2022

Substance number: 38040057980

Replaces Version: 10 / GB

Print date: 17.06.22

All components are contained in the AICS inventory.  
All components are contained in the ENCS inventory.  
All components are contained in the TSCA inventory or exempted.

### 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

### **Hazard statements listed in Chapter 3**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### **CLP categories listed in Chapter 3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
Resp. Sens. 1	Respiratory sensitization, Category 1
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### **Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.