

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

UFI :

RH92-J0DS-J009-P2F3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

Pad printing ink.

1.3. Details of the supplier of the safety data sheet

Name

COMEC ITALIA SRL

Full address

Piazzale del lavoro 149

District and Country

21044 Cavaria (VA)

ITALIA

Tel. +39 0331 219516

Fax +39 0331 216161

e-mail address of the competent person responsible for the Safety Data Sheet Supplier:

info@comec-italia.it

Edgardo Baggini

1.4. Emergency telephone number

For urgent inquiries refer to

**CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h) -
CENTRO ANTIVELENI POLICLINICO A.GEMELL ROMA Tel. 06/3054343 (24/24h) -**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

Serious eye damage, category 1

H318

Causes serious eye damage.

Specific target organ toxicity - single exposure, category 3

H336

May cause drowsiness or dizziness.

Hazardous to the aquatic environment, chronic toxicity, category 3

H412

Harmful to aquatic life with long lasting effects.

2.2. Label elements

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor.
P370+P378 In case of fire: use chemical powder, CO2 or dry send to extinguish.
P261 Avoid breathing dust, gas or vapours.

Contains: CYCLOHEXANONE
 2-METHOXY-1-METHYLETHYL ACETATE
 2-ETHOSSI-1-METHYL ETHYL ACETATE
 AROMATIC HYDROCARBONS, C9

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer
 Reaction product of BPA; possible contamination <0.05%

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
BUTYLGLYCOL ACETATE		
INDEX 607-038-00-2	22,5 \leq x < 24	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

EC 203-933-3		LD50 Oral: 1880 mg/kg, LD50 Dermal: 1500 mg/kg, STA Inhalation vapours: 11 mg/l
CAS 112-07-2		
REACH Reg. 01-2119475112-47xxxx		
ALUMINIUM POWDER (STABILIZED)		
INDEX 013-002-00-1	10,5 ≤ x < 12	Flam. Sol. 1 H228, Classification note according to Annex VI to the CLP Regulation: T
EC 231-072-3		
CAS 7429-90-5		
REACH Reg. 01-2119529243-45		
2-METHOXY-1-METHYLETHYL ACETATE		
INDEX 607-195-00-7	9 ≤ x < 10,5	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-603-9		
CAS 108-65-6		
REACH Reg. 01-2119475791-29-xxxx		
2-ETHOSSI-1-METHYL ETHYL ACETATE		
INDEX 603-177-00-8	6 ≤ x < 7	Flam. Liq. 3 H226, STOT SE 3 H336
EC 259-370-9		
CAS 54839-24-6		
REACH Reg. 01-2119475116-39xxxx		
AROMATIC HYDROCARBONS, C9		
INDEX -	3,5 ≤ x < 4	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC 918-668-5		
CAS -		
REACH Reg. 01-2119455851-35-xxxx		
HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, CYCLIC, <2% AROMATIC		
INDEX -	3,5 ≤ x < 4	Asp. Tox. 1 H304, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC 918-481-9		
CAS -		
REACH Reg. 01-2119457273-39-xxxx		
CYCLOHEXANONE		
INDEX 606-010-00-7	3 ≤ x < 3,5	Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Dam. 1 H318, Skin Irrit. 2 H315 LD50 Oral: 1535 mg/kg, LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h
EC 203-631-1		
CAS 108-94-1		
REACH Reg. 01-2119453616-35-xxxx		
Hydrocarbons, C10, aromatics, <1% naphthalene		
INDEX -	1,5 ≤ x < 2	Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066
EC 918-811-1		
CAS -		

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

REACH Reg. 01-2119463583-34-xxxx

4,4'-ISOPROPYLIDENEDIPHENOL

INDEX 604-030-00-0

$0 \leq x < 0,01$

Repr. 1B H360F, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=10

EC 201-245-8

CAS 80-05-7

REACH Reg. 2119457856-23-xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE
GLITTER, 77 RE GLITTER, 78 RE GLITTER,****SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

BGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,

COMEC ITALIA SRL

Revision nr. 5

Dated 15/11/2022

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Printed on 25/01/2023

Page n. 6/26

Replaced revision:4 (Dated: 11/01/2021)

CZE	Česká Republika	СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DNK	Danmark	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte.
ESP	España	MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ITA	Italia	Límites de exposición profesional para agentes químicos en España 2021
NLD	Nederland	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
PRT	Portugal	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	Arbetsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
ROU	România	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
SWE	Sverige	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
TUR	Türkiye	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
GBR	United Kingdom	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
EU	OEL EU	Kımyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
	TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
		Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/16/EC; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
		ACGIH 2021

BUTYLGLYCOL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	133	20	333	50	SKIN
TLV	CZE	130	19,5	300	45	SKIN
AGW	DEU	65	10	130 (C)	20 (C)	SKIN 11
MAK	DEU	66	10	132	20	SKIN Hinweis
TLV	DNK	134	20			SKIN E
VLA	ESP	133	20	333	50	SKIN
VLEP	FRA	66,5	10	333	50	
VLEP	ITA	133	20	333	50	SKIN
TGG	NLD	135		333		SKIN
VLE	PRT	133	20	333	50	SKIN
NDS/NDSch	POL	100		300		SKIN
TLV	ROU	133	20	333	50	SKIN
NGV/KGV	SWE	70	10	333	50	SKIN
ESD	TUR	133	20	333	50	SKIN
WEL	GBR	133	20	332	50	SKIN
OEL	EU	133	20	333	50	SKIN
TLV-ACGIH		131	20			
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,304		mg/l
Normal value in marine water				0,03		mg/l
Normal value for fresh water sediment				2,03		mg/l

COMEC ITALIA SRL

Revision nr. 5

Dated 15/11/2022

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Printed on 25/01/2023

Page n. 7/26

Replaced revision:4 (Dated: 11/01/2021)

Normal value for marine water sediment	0,203	mg/l
Normal value for water, intermittent release	0,56	mg/l
Normal value of STP microorganisms	90	mg/l
Normal value for the food chain (secondary poisoning)	60	mg/kg
Normal value for the terrestrial compartment	0,415	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	36 mg/kg/d	VND	4,3 mg/kg/d				
Inhalation	200 mg/m3	499 mg/m3	VND	80 mg/m3	333 mg/m3	773 mg/m3	VND	133 mg/m3
Skin		72 mg/kg bw/d	VND	102 mg/kg/d	102 mg/kg/d	27 mg/kg/d	VND	169 mg/kg/d

ALUMINIUM POWDER (STABILIZED)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	2				
MAK	DEU	4				INHAL
MAK	DEU	1,5				RESP
TLV	DNK	5				
TLV	DNK	2				RESP
VLA	ESP	1				RESP
VLEP	FRA	5				
NDS/NDSch	POL	2,5				INHAL
NGV/KGV	SWE	5				Som AI, Totaldamm
NGV/KGV	SWE	2				RESP Som AI
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		1	0,9			RESP AI

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0749	mg/l
Normal value of STP microorganisms	20	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,95 mg/kg bw/d				
Inhalation							3,72 mg/m3	3,72 mg/m3

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN

COMEC ITALIA SRL

Revision nr. 5

Dated 15/11/2022

Printed on 25/01/2023

Page n. 8/26

Replaced revision:4 (Dated: 11/01/2021)

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

TLV	CZE	270	49,14	550	100,1	SKIN	
AGW	DEU	270	50	270	50		
MAK	DEU	270	50	270	50		
TLV	DNK	275	50			SKIN	E
VLA	ESP	275	50	550	100	SKIN	
VLEP	FRA	275	50	550	100	SKIN	
VLEP	ITA	275	50	550	100	SKIN	
TGG	NLD	550					
VLE	PRT	275	50	550	100	SKIN	
NDS/NDSch	POL	260		520		SKIN	
TLV	ROU	275	50	550	100	SKIN	
NGV/KGV	SWE	275	50	550	100	SKIN	
ESD	TUR	275	50	550	100	SKIN	
WEL	GBR	274	50	548	100	SKIN	
OEL	EU	275	50	550	100	SKIN	

Predicted no-effect concentration - PNEC							
Normal value in fresh water				0,635	mg/l		
Normal value in marine water				0,0635	mg/l		
Normal value for fresh water sediment				3,29	mg/kg		
Normal value for marine water sediment				0,329	mg/l		
Normal value for water, intermittent release				6,35	mg/l		
Normal value of STP microorganisms				100	mg/l		
Normal value for the terrestrial compartment				0,29	mg/kg		

Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			33 mg/m3	33 mg/m3	550 mg/m3		VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

2-ETHOSSI-1-METHYL ETHYL ACETATE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	120	20	240	40	SKIN 14
MAK	DEU	120	20	240	40	SKIN Hinweis

Predicted no-effect concentration - PNEC						
Normal value in fresh water				2	mg/l	
Normal value in marine water				0,8	mg/l	
Normal value for fresh water sediment				8,2	mg/kg	
Normal value for marine water sediment				0,6	mg/kg	
Normal value for water, intermittent release				2	mg/l	
Normal value of STP microorganisms				62,5	mg/kg	

COMEC ITALIA SRL

Revision nr. 5

Dated 15/11/2022

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Printed on 25/01/2023

Page n. 9/26

Replaced revision:4 (Dated: 11/01/2021)

Normal value for the food chain (secondary poisoning) 117 mg/kg

Normal value for the terrestrial compartment 0,6 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	13,1 mg/kg				
Inhalation	VND	365 mg/m3	VND	181 mg/m3	VND	608 mg/m3	VND	302 mg/m3
Skin			VND	62 mg/kg			VND	103 mg/kg

AROMATIC HYDROCARBONS, C9

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	ITA	100	20			1,2,3 trimetilbenzene
OEL	EU	100	20			1,2,3 trimetilbenzene
TLV-ACGIH			25			1,2,3 trimetilbenzene

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg				11 mg/kg bw/d
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg			VND	25 mg/kg

HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, CYCLIC, <2% AROMATIC

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN
TLV-ACGIH		1200	184			

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				300 mg/kg/d				
Inhalation				900 mg/m3				
Skin				300 mg/kg/d				300 mg/kg/d

CYCLOHEXANONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	40,8	10	81,6	20	SKIN

COMEC ITALIA SRL

Revision nr. 5

Dated 15/11/2022

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Printed on 25/01/2023

Page n. 11/26

Replaced revision:4 (Dated: 11/01/2021)

Oral	VND	28 mg/kg/d			
Inhalation			3 mg/m3	VND	
Skin	VND	28 mg/kg/d	VND	45 mg/kg/d	

Traduci da: Indonesiano

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0032	mg/l
Normal value in marine water	0,0032	mg/l
Normal value for fresh water sediment	15,6	mg/kg
Normal value for water, intermittent release	0,0032	mg/l
Normal value of STP microorganisms	35	mg/l
Normal value for the terrestrial compartment	0,865	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,3 mg/kg bw/d						
Inhalation				4,4 mg/m3				17,8 mg/m3
Skin				13 mg/kg bw/d				25,5 mg/kg bw/d

HYDROM HYDROPHONE SILICATE

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
AGW	DEU	4		INHAL
MAK	DEU	4		INHAL

Alkyl (C12-14) dimethylamine

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00026	mg/l
Normal value in marine water	0,00003	mg/l
Normal value for fresh water sediment	1,25	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value for water, intermittent release	0,00026	mg/l
Normal value of STP microorganisms	0,13	mg/l
Normal value for the terrestrial compartment	1	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					1 mg/m3		1 mg/m3	

Alkyl (C16-C18) dimethylamine

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00026	mg/l
-----------------------------	---------	------

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Normal value in marine water	0,00003	mg/l
Normal value for fresh water sediment	1,25	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value for water, intermittent release	0,00026	mg/l
Normal value of STP microorganisms	0,13	mg/l
Normal value for the terrestrial compartment	1	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					1 mg/m3		1 mg/m3	

Alkyl (C12-16) dimethylamine

Predicted no-effect concentration - PNEC								
Normal value in fresh water					0,00026			
Normal value in marine water					0,00003			
Normal value for fresh water sediment					1,25			
Normal value for marine water sediment					0,125			
Normal value for water, intermittent release					0,00026			
Normal value of STP microorganisms					0,13			
Normal value for the terrestrial compartment					1			

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					1 mg/m3		1 mg/m3	

4,4'-ISOPROPYLIDENEDIPHENOL

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	2				INHAL		
TLV	CZE	2		5		INHAL		
AGW	DEU	5		5 (C)		INHAL		
TLV	DNK	2				E		
VLEP	FRA	2						
VLEP	ITA	2				INHAL		
VLEP	ITA	2				SKIN		
TGG	NLD	2				INHAL		
VLE	PRT	2				INHAL		
NDS/NDSch	POL	2				INHAL		
TLV	ROU	2				INHAL		
ESD	TUR	10						
WEL	GBR	2						
OEL	EU	2				INHAL		

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,018	mg/l
Normal value in marine water	0,016	mg/l
Normal value of STP microorganisms	320	mg/l
Normal value for the terrestrial compartment	3,7	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral						0,05 mg/kg bw/d		0,05 mg/kg bw/d
Inhalation	5 mg/m3	5 mg/m3	5 mg/m3	0,25 mg/m3		10 mg/m3		10 mg/m3
Skin		0,7 mg/kg bw/d		0,7 mg/kg bw/d		1,4 mg/kg bw/d		1,4 mg/kg bw/d

hexadecyldimethylamine		
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,00026	mg/l
Normal value in marine water	0,00003	mg/l
Normal value for fresh water sediment	1,25	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value for water, intermittent release	0,00026	mg/l
Normal value of STP microorganisms	0,13	mg/l
Normal value for the terrestrial compartment	1	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					1 mg/m3		1 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	various	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	$23 \leq T \leq 60$ °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

**PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE
GLITTER, 77 RE GLITTER, 78 RE GLITTER,****9.2. Other information**

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 51,96 %

VOC (volatile carbon) 33,12 %

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

CYCLOHEXANONE

Attacks various types of plastic materials.

May condense under the effect of heat to form resinous compounds.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

CYCLOHEXANONE

Risk of explosion on contact with: hydrogen peroxide, nitric acid, heat, mineral acids. May react violently with: oxidising agents. Forms explosive mixtures with: air.

10.4. Conditions to avoid

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

CYCLOHEXANONE

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances,strong acids,alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C10, aromatics, <1% naphthalene
Specific target organ toxicity (STOT) - single exposure:
NOAEC> 600 mg / kg Inhalation. Rat

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer

LD50 (Dermal):	> 2000 mg/kg Ratto / Rat
LD50 (Oral):	> 2000 mg/kg Ratto / Rat

BUTYLGLYCOL ACETATE

LD50 (Dermal):	1500 mg/kg Coniglio / Rabbit
LD50 (Oral):	1880 mg/kg Ratto / Rat
LC50 (Inhalation vapours):	0,4 mg/l/4h Ratto - Rat
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

ALUMINIUM POWDER (STABILIZED)

LC50 (Inhalation mists/powders):	> 5 mg/l Ratto / Rat (4h)
----------------------------------	---------------------------

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Coniglio / Rabbit
LD50 (Oral):	8500 mg/kg Ratto / Rat
LC50 (Inhalation vapours):	4345 ppm/6h Ratto / Rat

2-ETHOSSI-1-METHYL ETHYL ACETATE

LD50 (Dermal):	13,42 ml/Kg Coniglio / Rabbit
LD50 (Oral):	> 5000 mg/kg Ratto / Rat
LC50 (Inhalation vapours):	6,99 mg/l/4h Rat

AROMATIC HYDROCARBONS, C9

LD50 (Dermal):	> 3160 mg/kg Ratto / Rat
LD50 (Oral):	3492 mg/kg Ratto / Rat
LC50 (Inhalation vapours):	> 6193 mg/l/4h Ratto / Rat

HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, CYCLIC, <2% AROMATIC

LD50 (Dermal):	> 2000 mg/kg bw Rat
LD50 (Oral):	> 5000 mg/kg bw Rat

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

LC50 (Inhalation vapours): > 5000 mg/m3 8h Rat

CYCLOHEXANONE

LD50 (Dermal): 1100 mg/kg 794 - 3160 / Coniglio / Rabbit
 LD50 (Oral): 1535 mg/kg Ratto / Rat
 LC50 (Inhalation vapours): 11 mg/l/4h Ratto / Rat (4h)

Hydrocarbons, C10, aromatics, <1% naphthalene

LD50 (Dermal): > 2000 mg/kg Coniglio / Rabbit
 LD50 (Oral): 6318 mg/kg Ratto / Rat
 LC50 (Inhalation vapours): > 4688 mg/kg/4h Ratto / Rat

4,4'-ISOPROPYLIDENEDIPHENOL

LD50 (Dermal): 3000 mg/kg Rabbit
 LD50 (Oral): 5000 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Hydrocarbons, C10, aromatics, <1%
naphtalene

LC50 - for Fish	> 2 mg/l/96h
EC50 - for Crustacea	> 3 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h

HYDROCARBONS, C10-C13, n-alkanes,
isoalkanes, CYCLIC, <2% AROMATIC

LC50 - for Fish	> 1000 mg/l/96h Oncorhynchus mykiss OECD 203
EC50 - for Crustacea	> 1000 mg/l/48h Daphnia magna

AROMATIC HYDROCARBONS, C9

LC50 - for Fish	> 9,2 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 3,2 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 2,9 mg/l/72h Pseudokirchneriella subcapitata

2-METHOXY-1-METHYLETHYL ACETATE

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

LC50 - for Fish	134 mg/l/96h Pesce, Oncorhynchus mykiss OECD 203
EC50 - for Crustacea	> 500 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h Selenastrum capricornutum OECD 201
Chronic NOEC for Fish	47,5 mg/l Oryzias latipes 14 gg OECD 204
Chronic NOEC for Crustacea	100 mg/l Daphnia magna 21 gg OECD 202

2-ETHOSSI-1-METHYL ETHYL ACETATE

LC50 - for Fish	140 mg/l/48h Oncorhynchus mykiss (test 48h)
EC50 - for Crustacea	110 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Scenedesmus subspicatus

CYCLOHEXANONE

LC50 - for Fish	527 mg/l/96h 527 - 732 / Pimephales promelas
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Scenedesmus subspicatus

BUTYLGLYCOL ACETATE

LC50 - for Fish	> 20 mg/l/96h Fish 20-40 mg/kg (48h)
EC50 - for Crustacea	145 mg/l/24h Daphnia Magna (24h)
EC50 - for Algae / Aquatic Plants	1570 mg/l/72h Scenedesmus subspicatus

4,4'-ISOPROPYLIDENEDIPHENOL

LC50 - for Fish	9,4 mg/l/96h Menidia menidia
EC50 - for Crustacea	10,2 mg/l/48h Daphnia magna
Chronic NOEC for Fish	0,016 mg/l Pimephales promelas
Chronic NOEC for Crustacea	1,8 mg/l Daphnia magna

12.2. Persistence and degradability

Hydrocarbons, C10, aromatics, <1%
naphthalene
Solubility in water immiscibile in H2O mg/l

Rapidly degradable
HYDROCARBONS, C10-C13, n-alkanes,
isoalkanes, CYCLIC, <2% AROMATIC

Rapidly degradable
AROMATIC HYDROCARBONS, C9

Rapidly degradable
ALUMINIUM POWDER (STABILIZED)

Solubility in water 0 mg/l

Degradability: information not available

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable
OECD GI 301F 83% 10 d

2-ETHOSSI-1-METHYL ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

Activated sludge - 89%/15 d - 100%/28 d
CYCLOHEXANONE

Solubility in water 86 mg/l

Rapidly degradable
BUTYLGLYCOL ACETATE

Solubility in water 15000 mg/l

Rapidly degradable
4,4'-ISOPROPYLIDENEDIPHENOL

Solubility in water 301 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

BCF 100

2-ETHOSSI-1-METHYL ETHYL ACETATE

Partition coefficient: n-octanol/water 0,76

BCF 3,162

CYCLOHEXANONE

Partition coefficient: n-octanol/water 0,86

BUTYLGLYCOL ACETATE

Partition coefficient: n-octanol/water 1,51

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: n-octanol/water 3,4

BCF 73

12.4. Mobility in soil

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: soil/water 1,7

2-ETHOSSI-1-METHYL ETHYL ACETATE

Partition coefficient: soil/water 1

CYCLOHEXANONE

Partition coefficient: soil/water 1,18

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: soil/water 2,95

12.5. Results of PBT and vPvB assessment

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1210

14.2. UN proper shipping name

ADR / RID: PRINTING INK

IMDG: PRINTING INK

IATA: PRINTING INK

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 163, 367		
IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
 Point 3 - 40

Contained substance
 Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Flam. Sol. 1	Flammable solid, category 1
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H228	Flammable solid.
H360F	May damage fertility.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.

PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE GLITTER, 77 RE GLITTER, 78 RE GLITTER,

H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)

**PLT 4 METAL 1: 75 RE, 76 RE, 77 RE, 78 RE, 75 RE GLITTER, 76 RE
GLITTER, 77 RE GLITTER, 78 RE GLITTER,**

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 14 / 15 / 16.