#### **COMEC ITALIA SRL** Dated 19/02/2024 First compilation Printed on 21/02/2024 CATALIZZATORE: PLHG. Page n. 1/15

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

CATALIZZATORE: PLHG, Product name UFI: 4253-X0PF-6006-2JH1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Screen printing hardener. Intended use

#### 1.3. Details of the supplier of the safety data sheet

**COMEC ITALIA SRL** Full address Piazzale del lavoro 149 District and Country 21044 Cavaria (VA) **ITALIA** 

Tel. +39 0331 219516 Fax +39 0331 216161

e-mail address of the competent person

responsible for the Safety Data Sheet info@comec-italia.it Supplier: Edgardo Baggini

#### 1.4. Emergency telephone number

For urgent inquiries refer to Centro Antiveleni di Milano 02 66101029

(Niguarda Ca Granda - Milano) Centro Antiveleni di Pavia 0382 24444 (Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300

(Papa Giovanni XXIII - Bergamo) Centro Antiveleni di Verona 800 011858

(AOUI - Verona)

Centro Antiveleni di Firenze 055 7947819

(Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343

(Agostino Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000

(Umberto I - Roma)

Centro Antiveleni di Roma 06 68593726 (Ospedale pediatrico Bambino Gesu - Roma) Centro Antiveleni di Napoli 081 5453333

(Antonio Cardarelli - Napoli)

Centro Antiveleni di Foggia 800 183459 (Azienda ospedaliera universitaria - Foggia)

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and

CATALIZZATORE: PLHG,

supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Revision nr. 1

Dated 19/02/2024 First compilation

Printed on 21/02/2024

Page n. 2/15

Hazard classification and indication:

Acute toxicity, category 4 H332 Harmful if inhaled.

Specific target organ toxicity - repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated

exposure.

Serious eye damage, category 1 H318 Causes serious eye damage. Skin sensitization, category 1 H317 May cause an allergic skin reaction.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:







Signal words: Danger

Hazard statements:

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P280 Wear protective gloves / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor.

P261 Avoid breathing dust, gas or vapours.

P362+P364 Take off contaminated clothing and wash it before reuse.

Contains: Aminoethylamino propyltrimethoxy silane

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

#### **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Revision nr. 1

Dated 19/02/2024

First compilation

Page n. 3/15

Printed on 21/02/2024

**CATALIZZATORE: PLHG,** 

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

Aminoethylamino

propyltrimethoxy silane

INDEX - 96 ≤ x < 100 Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318, Skin Sens. 1 H317

EC 217-164-6 STA Inhalation vapours: 11 mg/l

CAS 1760-24-3

REACH Reg. 01-2119970215-39-

xxxx

**METHANOL** 

INDEX 603-001-00-X 0,8 ≤ x < 0,9 Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3

H331, STOT SE 1 H370 EC 200-659-6 STOT SE 2 H371: ≥ 3%

CAS 67-56-1 STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation vapours: 3

mg/l, STA Inhalation mists/powders: 0,501 mg/l

REACH Reg. 01-2119433307-44-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Choose the most appropriate extinguishing equipment for the specific case.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE The product is neither flammable nor combustible.

#### 5.3. Advice for firefighters

COMEC ITALIA SRL	Revision nr. 1
	Dated 19/02/2024
	First compilation
CATALIZZATORE: PLHG,	Printed on 21/02/2024
	Page n. 4/15

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

#### **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

#### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

CATALIZZATORE: PLHG,

Revision nr. 1

Dated 19/02/2024

First compilation

Printed on 21/02/2024

Page n. 5/15

BGR

CZE

DFU

NLD

PRT

POL

ROU

SWE

EU

България

Deutschland

Nederland

Portugal

Polska

România

Sverige

OEL EU

Normal value for the terrestrial compartment

НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,

СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари

Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se

Česká Republika stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte.

MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher

Arbeitsstoffe, Mitteilung 56

DNK Danmark Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019

ESP Límites de exposición profesional para agentes químicos en España 2021 España FRA France

Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste

lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit

Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes

químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie

w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w

środowisku pracy

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea

si completarea hotărârii guvernului nr. 1.093/2006 Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS

TUR Türkiye Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733 GBR United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983;

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

mg/kg

2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

0,0085

bw/d

TLV-ACGIH **ACGIH 2021** 

Aminoethylamino propyltrimethoxy silane Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,062	mg/l	
Normal value in marine water	0,0062	mg/l	
Normal value for fresh water sediment	0,22	mg/kg	
Normal value for marine water sediment	0,022	mg/kg	
Normal value for water, intermittent release	0,62	mg/l	
Normal value of STP microorganisms	25	mg/l	

Health - Derived no-effect level - DNEL / DMEL								
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Oral				2,5 mg/kg				
				bw/d				
Inhalation	NPI	NPI	VND	8,7 mg/m3	NPI	NPI	VND	35,3 mg/m3
Skin	VND	17 mg/kg bw/d	VND	2,5 mg/kg	VND	5 mg/kg bw/d	VND	5 mg/kg bw/d

METHANOL								
Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	8	
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	260	200			SKIN		
TLV	CZE	250	187,75	1000	751	SKIN		
AGW	DEU	270	200	1080	800	SKIN		
MAK	DEU	130	100	260	200	SKIN		
TLV	DNK	260	200			SKIN	Е	
VLA	ESP	266	200			SKIN		

Revision nr. 1

Dated 19/02/2024

First compilation

Page n. 6/15

Printed on 21/02/2024

CATALIZZATORE: PLHG,

VLEP	FRA	260	200	1300	1000	SKIN	11	
VLEP	ITA	260	200			SKIN		
TGG	NLD	133				SKIN		
VLE	PRT	260	200			SKIN		
NDS/NDSCh	POL	100		300		SKIN		
TLV	ROU	260	200			SKIN		
NGV/KGV	SWE	250	200	350 (C)	250 (C)	SKIN		
ESD	TUR	260	200			SKIN		
WEL	GBR	266	200	333	250	SKIN		
OEL	EU	260	200					
TLV-ACGIH		262	200	328	250	SKIN		
Predicted no-effect conc	entration - PNEC							
Normal value in fresh wa	nter			154	mg/	1		
Normal value in marine v	water			15,4	mg/	Ί		
Normal value for fresh w	ater sediment			570,4	mg/	'kg		
Normal value for water, i	ntermittent release			1540	mg/	Ί		
Normal value of STP mid	croorganisms			100	mg/	Ί		
Normal value for the terr	estrial compartment			23,5	mg/	'ka		

Health - Derived no-effect i	evel - DNEL / DI	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation	50 mg/m3	50 mg/m3	50 mg/m3	50 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3	260 mg/m3
Skin	VND	8 mg/kg/d	VND	8 mg/kg/d	VND	40 mg/kg/d	VND	40 mg/kg/d

Legend:

(C) = CEILING : INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

## COMEC ITALIA SRL Revision nr. 1 Dated 19/02/2024 First compilation Printed on 21/02/2024 Page n. 7/15

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

#### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	straw yellow	
Odour	amino	
Melting point / freezing point	-20 °C	
Initial boiling point	259 °C	
Flammability	incombustible	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	138 °C	
Auto-ignition temperature	> 300 °C	
Decomposition temperature	not available	
рН	10	
Kinematic viscosity	not available	
Dynamic viscosity	6 mPass@20°C	
Solubility	immiscible	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,03	
Relative vapour density	>1	
Particle characteristics	not applicable	

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

# COMEC ITALIA SRL Revision nr. 1 Dated 19/02/2024 First compilation Printed on 21/02/2024 Page n. 8/15

9.2.2. Other safety characteristics

Information not available

#### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

#### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Aminoethylamino propyltrimethoxy silane Acute Oral Toxicity: LD 50 rat> 2000 mg / kg Acute dermal toxicity: LD 50 rabbit>2000 mg / kg.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Aminoethylamino propyltrimethoxy silane

Irritating to skin: Rabbit, no skin irritation OECD TG 404 Irritating to eyes: Rabbit, highly irritating OECD TG 405

Sensitization: guinea pig, positive. May cause sensitization by skin contact, OECD 429 (LLNA)

Repeated dose toxicity: Oral rat, NOEL >= 500 mg/Kg (28 gg), OECD 422.

Revision nr. 1

Dated 19/02/2024 First compilation

Printed on 21/02/2024

Page n. 9/15

**CATALIZZATORE: PLHG,** 

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Information not available

#### **ACUTE TOXICITY**

ATE (Inhalation - mists / powders) of the mixture:

ACUTE TOX. 4
ATE (Inhalation - vapours) of the mixture:

ACUTE TOX. 4
ATE (Inhalation - gas) of the mixture:

ACUTE TOX. 4
ATE (Oral) of the mixture:

ACUTE TOX. 4
ATE (Dermal) of the mixture:

>2000 mg/kg
>2000 mg/kg

Aminoethylamino propyltrimethoxy silane

 LD50 (Dermal):
 > 2000 mg/kg Rabbit

 LD50 (Oral):
 2400 mg/kg Rat

 LC50 (Inhalation vapours):
 1,49 mg/l/4h Ratto / Rat

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

METHANOL

LD50 (Dermal): 11700 mg/kg Coniglio / Rabbit

STA (Dermal): 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): > 1000 mg/kg Ratto / Rat

STA (Oral): 100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

### Revision nr. 1 **COMEC ITALIA SRL** Dated 19/02/2024 First compilation Printed on 21/02/2024 **CATALIZZATORE: PLHG,** Page n. 10/15 SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class SERIOUS EYE DAMAGE / IRRITATION Causes serious eye damage RESPIRATORY OR SKIN SENSITISATION Sensitising for the skin GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class CARCINOGENICITY Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class STOT - REPEATED EXPOSURE May cause damage to organs ASPIRATION HAZARD

### COMEC ITALIA SRL Revision nr. 1 Dated 19/02/2024 First compilation Printed on 21/02/2024 Page n. 11/15

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

#### **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

Aminoethylamino propyltrimethoxy silane

Toxicity to algae: CE50, Pseudokirchneriella subcapitata, 8,8 mg/l (96h)

NOEC, Pseudokirchneriella subcapitata, 3,1 mg/l.

Aminoethylamino propyltrimethoxy silane

LC50 - for Fish 597 mg/l/96h Lepomis macrochirus

 EC50 - for Crustacea
 81 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 126 mg/l/72h

 LC10 for Fish
 344 mg/l/96h

**METHANOL** 

LC50 - for Fish 15400 mg/l/96h EC50 - for Crustacea > 10000 mg/l/48h

#### 12.2. Persistence and degradability

Aminoethylamino propyltrimethoxy silane

NOT rapidly degradable

METHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

#### 12.3. Bioaccumulative potential

METHANOL

Partition coefficient: n-octanol/water -0,77
BCF 0,2

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

COMEC ITALIA SRL	Revision nr. 1
	Dated 19/02/2024
	First compilation
CATALIZZATORE: PLHG,	Printed on 21/02/2024
•	Page n. 12/15

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number		
not applicable		
14.2. UN proper shipping name		

#### 14.3. Transport hazard class(es)

not applicable

not applicable

#### 14.4. Packing group

not applicable

	COMEC ITALI	IA SRL	Revision nr. 1
			Dated 19/02/2024
			First compilation
C	<b>ATALIZZATOR</b>	E: PLHG,	Printed on 21/02/2024
			Page n. 13/15
14.5. Environmental hazards			
not applicable			
14.6. Special precautions for user			
not applicable			
14.7. Maritime transport in bulk accord	ling to IMO instrument	ts	
Information not relevant			
SECTION 15. Regulatory in	formation		
15.1. Safety, health and environment	al regulations/legislat	ion specific for the substance or mixture	
Seveso Category - Directive 2012/18/EU:	None		
Restrictions relating to the product or con	tained substances purs	suant to Annex XVII to EC Regulation 1907/2006	
Product Point	3 - 40		
Contained substance			
Point	69	METHANOL REACH Reg.: 01- 2119433307-44-xxxx	
Regulation (EU) 2019/1148 - on the mark	eting and use of explos	sives precursors	
not applicable			
Substances in Candidate List (Art. 59 RE	ACH)		
On the basis of available data, the produc	ot does not contain any	SVHC in percentage ≥ than 0,1%.	
Substances subject to authorisation (Ann	ex XIV REACH)		
None			
Substances subject to exportation reporting	ng pursuant to Regulati	ion (EU) 649/2012:	
None			
Substances subject to the Rotterdam Cor	<u>nvention:</u>		
None			

#### **COMEC ITALIA SRL** Dated 19/02/2024 First compilation Printed on 21/02/2024 **CATALIZZATORE: PLHG,** Page n. 14/15

Substances subject to the Stockholm Convention:

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2 Acute Tox. 3 Acute toxicity, category 3

STOT SE 1 Specific target organ toxicity - single exposure, category 1

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eve Dam. 1 Serious eye damage, category 1 Skin Sens. 1 Skin sensitization, category 1 H225

Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage. H317 May cause an allergic skin reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

#### Revision nr. 1 **COMEC ITALIA SRL** Dated 19/02/2024 First compilation Printed on 21/02/2024 CATALIZZATORE: PLHG. Page n. 15/15

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament

- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EŬ) 2019/Ì148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP) 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP) 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
   Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

For information on any exposure scenarios of the substances present in the mixture, contact Sericom Italia srl.