

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PLT 64

· Article number: PLT 64

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant

information available.

· Application of the substance / the mixture

Printing inks

Printig ink and / or printing ink related material

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

COMEC ITALIA SRL

- · Piazzale del lavoro 149
- · 21044 Cavaria (VA) ITALIA
- · Tel. +39 0331 219516
- · Fax +39 0331 216161
- · info@comec-italia.it
- · Edgardo Baggini
- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h)

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Version number 7 (replaces version 6) Printing date 28.02.2023 Revision: 28.02.2023

Trade name: PLT 64

· Hazard pictograms

(Contd. of page 1)









· Signal word Danger

### · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Hydrocarbon, C10, aromatics, <1% naphthalene

hydrocarbons, C9, aromates

#### · Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways. H304 Toxic to aquatic life with long lasting effects. H411

#### **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smokina.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing P280

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Do NOT induce vomiting. P331

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

#### · Additional information:

Contains isobutyl methacrylate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-95-6 Index number: 649-356-00-4 Reg.nr.: 01-2119486773-24-xxxx 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226; SASP. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	≥20-<25%
CAS: 1189173-42-9 EC number: 918-811-1 Reg.nr.: 01-2119463583-xxxx	Hydrocarbon, C10, aromatics, <1% naphthalene Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥10-<20%

(Contd. on page 3)

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

		Contd. of page 2)
CAS: 64742-95-6	hydrocarbons, C9, aromates	2.5-10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
	isobutyl methacrylate  Flam. Liq. 3, H226; Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335	≥0.1-<0.5%
_ I	propylidynetrimethanol  Repr. 2, H361f	≥0-<0.5%

#### · Additional information:

Benzene content measured as impurities in Solvent-Naphta is below < 0,1% thus requiring no extra labeling. For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately rinse with water.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

#### **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

(Contd. on page 4)

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page 3)

#### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide floor trough without outlet.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm

Long-term value: 275 mg/m<sup>3</sup>, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not necessary if room is well-ventilated.
- Hand protection



(Contd. on page 5)

Version number 7 (replaces version 6) Printing date 28.02.2023 Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Eye/face protection



Solubility

Goggles recommended during refilling

## **SECTION 9: Physical and chemical properties**

• 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling >150 °C (>302 °F)

· Flammability Flammable.

Lower and upper explosion limit · Lower: 0.7 Vol %

· Upper: 7.5 Vol % 48 °C (118.4 °F) (Abel Pensky) · Flash point:

· Ignition temperature: 315 °C (599 °F)

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C (68 °F): 3,500-4,500 mPas

· water:

Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C (68 °F): 5 hPa (3.8 mm Hg) · Density and/or relative density

Density at 20 °C (68 °F): **1.58-**1.67 g/cm<sup>3</sup> (**13.19-**13.94 lbs/gal)

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page 5)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

Important information on protection of health and environment, and on safety.

Auto impition toward vertices

· **Auto-ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

**VOC (EC)** 47.89-47.91 %

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard

classes

· Explosives
· Flammable gases
· Aerosols
· Oxidising gases
· Cases under pressure

· Void
· Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable

Substances and mixtures, which emit flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page 6)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

CAS: 556-67-2 octamethylcyclotetrasiloxane

List II, III

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 03 12\* waste ink containing hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

- EU

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page 7)

ADR, IMDG, IATA	UN1210
14.2 UN proper shipping name ADR	1210 PRINTING INK, ENVIRONMENTAI HAZARDOUS
IMDG IATA	PRINTING INK, MARINE POLLUTANT PRINTING INK
14.3 Transport hazard class(es)	
ADR	
Class Label	3 Flammable liquids. 3
IMDG	
Class	3 Flammable liquids.  Not restricted good <450l according to IMDG 2.3.2.5
Label	3
IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardou substances: Solvent naphtha (petroleum), light arom.
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 30
EMS Number: Stowage Category	F-E,S-D A

(Contd. on page 9)

Printing date 28.02.2023 Version number 7 (replaces version 6) Revision: 28.02.2023

Trade name: PLT 64

(Contd. of page
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
3
D/E
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN 1210 PRINTING INK, 3, III, ENVIRONMENTALL HAZARDOUS

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

E١

Version number 7 (replaces version 6) Revision: 28.02.2023 Printing date 28.02.2023

Trade name: PLT 64

(Contd. of page 9)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

Date of previous version: 24.01.2023 · Version number of previous version: 6

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2