Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PLT 65 UV

· Article number: PLT 65 UV

 \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Printing inks
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

COMEC ITALIA SRL, Piazzale del Lavoro 149, 21044 Cavaria (VA), ITALY

- · Tel. +39 331 219516 Fax +39 331 216161
- · info@comec-italia.it
- · Edgardo Baggini
- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h) CENTRO ANTIVELENI POLICLINICO

A.GEMELL ROMA Tel. 06/3054343 (24/24h) -

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Dipentaerythritolhexaacrylat

2-hydroxyethyl methacrylate

2-phenoxyethyl acrylate

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

tripropylene glycol diacrylate

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

hexamethylene diacrylate

glycerol, propoxylated, esters with acrylic acid

4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

2,2-bis(acryloyloxymethyl)butyl acrylate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-butyl acetate	10-25%
EINECS: 204-658-1 Index number: 607-025-00-1	♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	
CAS: 29570-58-9	Dipentaerythritolhexaacrylat © Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%
CAS: 327622-75-3	Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and 1,3,5-tris(2-hydroxyethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 48145-04-6	2-phenoxyethyl acrylate Aquatic Chronic 2, H411; Skin Sens. 1, H317	1-2.5%
CAS: 163702-01-0 ELINCS: 402-990-3	Oligo[2-hydroxy-2-methyl-1-[4-(1-methylvinyl)phenyl]propanone]	1-2.5%
CAS: 63225-53-6	2-[[(butylamino)carbonyl]oxy]ethyl acrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-2.5%
CAS: 7473-98-5 EINECS: 231-272-0	2-hydroxy-2-methylpropiophenone Output Description: Des	1-2.5%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide Repr. 2, H361f	1-2.5%

(Contd. on page 3)

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

040 04500 04 4		d. of page	
CAS: 24599-21-1	2-(phosphonooxy)ethyl methacrylate	1-2.5%	
EINECS: 246-342-6	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 32435-46-4	bis(methacryloyloxyethyl) hydrogen phosphate	1-2.5%	
EINECS: 251-040-2	(1) Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 5888-33-5	exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	1-2.5%	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
CAS: 84434-11-7	ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	1-2.5%	
	Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Sens. 1, H317		
CAS: 157811-87-5	Siloxanes and silicones, di-Me, hydrogen-terminated, reaction products with pentaerythritol tetraacrylate © Eye Irrit. 2, H319	1-2.5%	
CAS: 954-16-5	2,4,6-trimethylbenzophenone	<1%	
ELINCS: 403-150-9 Index number: 606-044-00-2	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Eye Irrit. 2, H319		
CAS: 42978-66-5	tripropylene glycol diacrylate	<0.5%	
EINECS: 256-032-2	Aquatic Chronic 2, H411; 🔥 Skin Irrit. 2, H315; Eye Irrit. 2,		
Index number: 607-249-00-X	H319; Skin Sens. 1, H317; STOT SE 3, H335		
CAS: 162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	<0.5%	
ELINCS: 423-340-5	Skin Sens. 1, H317; Aquatic Chronic 4, H413		
Index number: 015-189-00-5	Similaria in the control of the cont		
CAS: 13048-33-4	hexamethylene diacrylate	<0.5%	
EINECS: 235-921-9	Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ♦ Skin		
Index number: 607-109-00-8	Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 52408-84-1	glycerol, propoxylated, esters with acrylic acid	<0.5%	
	♠ Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 55818-57-0	4,4'-isopropylidenediphenol, oligomeric reaction products with	<0.5%	
	1-chloro-2,3-epoxypropane, esters with acrylic acid	10.07	
	• Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;		
	Aquatic Chronic 4, H413		
CAS: 15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	<0.5%	
EINECS: 239-701-3	• Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10.07	
Index number: 607-111-00-9	♥ Simi mit. 2, 11010, Eyo mit. 2, 11010, Olim Ocho. 1, 11017		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

· Respiratory protection:

(Contd. of page 4)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

• Flash point: 44 °C (111.2 °F) (Abel Pensky)

· Ignition temperature: 370 °C (698 °F)

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 1.2 Vol % Upper: 7.5 Vol %

· Vapour pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)

· **Density:** Not determined.

(Contd. on page 6)

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

(Contd. of page 5)

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Viscosity:

Dynamic: Not determined.

VOC (EC) 15.37 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 03 12* waste ink containing hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1210	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1210 PRINTING INK PRINTING INK	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class · Label	3 Flammable liquids.3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: · Marine pollutant:	No	
 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E,S-D A	
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
· Transport/Additional information:		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
· Transport category · Tunnel restriction code	3 D/E	
	(Contd. on page 8)	

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

(Contd. of page 7)

·IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1210 PRINTING INK, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eve irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- · Department issuing SDS: Product safety department
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

(Contd. on page 9)

(Contd. of page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2019 Version number 3 Revision: 08.01.2019

Trade name: PLT 65 UV

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 1. Hazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard — Category 4

ΕU