

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Print date: 17.06.22 Substance number: 38040057970 Replaces Version: 12 / GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PLT 2 WHITE 970

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Pad printing ink

Identified Uses

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU₂2 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

Chemical production or refinery in closed process without likelihood of exposure PROC1

or processes with equivalent containment conditions.

Chemical production or refinery in closed continuous process with occasional PROC2

controlled exposure or processes with equivalent containment conditions

Manufacture or formulation in the chemical industry in closed batch processes PROC3

with occasional controlled exposure or processes with equivalent containment

condition

PROC4 Chemical production where opportunity for exposure arises

Mixing or blending in batch processes PROC5

Transfer of substance or mixture (charging and discharging) at nondedicated PROC8a

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing Non industrial spraving PROC11

Treatment of articles by dipping and pouring PROC13 Manual activities involving hand contact PROC19

Industrial use of processing aids in processes and products, not becoming part of ERC4

articles

Wide dispersive indoor use of processing aids in open systems ERC8a ERC8d Wide dispersive outdoor use of processing aids in open systems

Uses advised against

Consumer uses: Private households (= general public = consumers) **SU21**

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

COMEC ITALIA SRL Piazzale del lavoro 149 21044 Cavaria (VA)

ITALIA

Tel. +39 0331 219516 Fax +39 0331 216161

E-mail address of person responsible for this SDS

info@comec-italia.it Edgardo Baggini

1.4. Emergency telephone number

CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h) - CENTRO ANTIVELENI POLICLINICO A.GEMELL ROMA Tel. 06/3054343 (24/24h) -

SECTION 2: Hazards identification ***

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 Eye Dam. 1 H318 Aquatic Chronic 3 H412

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms ***





Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour. H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Cyclohexanone

EUH208 Contains Phthalic anhydride, May produce an allergic reaction.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Pad printing ink based on polyester resins and on solvents

Hazardous ingredients

Solvent naphtha (petroleum), light arom.

CAS No. 64742-95-6 EINECS no. 265-199-0

Registration no. 01-2119455851-35 (LIST NUMBER 918-668-5) Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

STOT SE 3 H335 Asp. Tox. 1 H304 Aquatic Chronic 2 H411

Cyclohexanone

CAS No. 108-94-1 EINECS no. 203-631-1

Registration no. 01-2119453616-35

Concentration >= 3 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H332 Flam. Liq. 3 H226 Acute Tox. 4 H302 Acute Tox. 4 H312 Eye Dam. 1 H318 Skin Irrit. 2 H315

2-Methoxy-1-methylethyl acetate

CAS No. 108-65-6 EINECS no. 203-603-9

Registration no. 01-2119475791-29

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

Propylidynetrimethanol

CAS No. 77-99-6 EINECS no. 201-074-9

Registration no. 01-2119486799-10

Concentration >= 0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)

Repr. 2 H361fd

Phthalic anhydride

CAS No. 85-44-9 EINECS no. 201-607-5

EINECS 110. 201-607-5

Concentration >= 0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)

 Skin Irrit. 2
 H315

 Skin Sens. 1
 H317

 Eye Dam. 1
 H318

 STOT SE 3
 H335

 Acute Tox. 4
 H302

 Resp. Sens. 1
 H334

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eve contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); dense black smoke; Hydrogen chloride (HCl)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances)

Temperature class T2

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Pad printing ink

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

2-Methoxy-1-methylethyl acetate

List EH40 Type WEL

Value 274 mg/m³ 50 ppm(V) Short term exposure limit 548 mg/m³ 100 ppm(V)

Skin resorption / sensibilisation: Sk; Status: 2011

Cyclohexanone

List EH40 Type WEL

Value 10 ppm(V)
Short term exposure limit 20 ppm(V)

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Skin resorption / sensibilisation: Sk; Status: 2005

Mesitylene

List EH40 Type WEL

Value 125 mg/m³ 25 ppm(V)

Status: 2011

1,2,4-Trimethylbenzene

List EH40 Type WEL

Value 125 mg/m³ 25 ppm(V)

Status: 2011

Phthalic anhydride

List EH40 Type WEL

Value 4 mg/m³
Short term exposure limit 12 mg/m³

Status: 2011

Derived No/Minimal Effect Levels (DNEL/DMEL)

2-Methoxy-1-methylethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 796 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 275 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 320 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Systemic effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Local effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects

Concentration 36 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Lifetime
Route of exposure inhalative
Mode of action Local effects

Concentration 550 mg/m³

Solvent naphtha (petroleum), light arom.

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 32 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 150 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 25 mg/kg/d

Cyclohexanone

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 40 mg/m³

Type of value Derived No Effect Level (DNEL)

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Reference group

Duration of exposure

Route of exposure

Mode of action

Systemic effects

Concentration 80 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consequential

Worker

Long term
inhalative
Local effects

Concentration 40 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Concentration

Worker

Short term
inhalative
Local effects

Concentration 80 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 4 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure dermal

Mode of action Systemic effects

Concentration 4 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure

Route of exposure

Mode of action

Long term
inhalative
Systemic effects

Concentration 10 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 20 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term
Route of exposure inhalative
Mode of action Local effects

Concentration 20 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Route of exposure inhalative
Mode of action Local effects

Concentration 40 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 1 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term Route of exposure dermal

Mode of action Systemic effects

Concentration 1 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term

Route of exposure oral

Mode of action Systemic effects

Concentration 1,5 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term Route of exposure oral

Mode of action Systemic effects

Concentration 1,5 mg/kg/d

Phthalic anhydride

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 32,2 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 10 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 8,6 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Duration of exposure Long term

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Route of exposure dermal

Mode of action Systemic effects

Concentration 5 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 5 mg/kg

Propylidynetrimethanol

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Long term
inhalative

Systemic effects

Concentration 3,3 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 0,94 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Systemic effects

Concentration 0,58 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 0,34 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 0,34 mg/kg/d

Predicted No Effect Concentration (PNEC)

2-Methoxy-1-methylethyl acetate

Reference substance 2-Methoxy-1-methylethyl acetate

Type of value PNEC Type Freshwater

Concentration 0,635 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 3,29 mg/kg

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Type of value PNEC Type Soil

Concentration 0,29 mg/kg

Source Literature value

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 100 mg/l

Source Literature value

Type of value PNEC

Type Marine sediment

Concentration 0,329 mg/kg

Source Literature value

Type of value PNEC Saltwater

Concentration 0,0635 mg/l

Cyclohexanone

Type of value PNEC
Type Freshwater

Concentration 0,033 mg/l

Type of value PNEC
Type Saltwater

Concentration 0,003 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 0,249 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 0,025 mg/kg

Type of value PNEC Type Soil

Concentration 0,03 mg/kg

Phthalic anhydride

Type of value PNEC
Type Freshwater

Concentration 1 mg/l

Type of value PNEC Saltwater

Concentration 0,1 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 5,6 mg/l

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Type of value PNEC
Type Sediment

Concentration 3,8 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 0,38 mg/kg

Type of value PNEC Type Soil

Concentration 0,173 mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Pasty
Colour coloured
Odour solvent-like

Odour threshold

Remarks No data available

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

pH value

Remarks Not applicable

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 148 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Value 45 °C

Method ASTM D 6450 (CCCFP)

Evaporation rate (ether = 1):

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,7 %(V)
Upper explosion limit appr. 10,8 %(V)

Source Literature value

Vapour pressure

Value appr. 4 hPa

Temperature 20 °C

Method calculated

Vapour density

Remarks not determined

Density

Value 1,650 g/cm³

Temperature 20 °C

Method DIN EN ISO 2811

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 315 °C

Source Literature value

Efflux time

Value > 150 s

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known

9.2. Other information

Other information

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

ATE > 2.000 mg/kg Method calculated value (Regulation (EC) No. 1272/2008)

Acute oral toxicity (Components)

Cyclohexanone

Species rat

LD50 1620 mg/kg

Acute dermal toxicity

ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)

Acute inhalational toxicity

ATE > 20 mg/l

Administration/Form Vapors

Method calculated value (Regulation (EC) No. 1272/2008)
ATE > 5 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

Cyclohexanone

Species rat

LC50 > 6,2 mg/l

Duration of exposure 4 h

Administration/Form Vapors

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

2-Methoxy-1-methylethyl acetate

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Species rabbit evaluation non-irritant

Serious eye damage/irritation

evaluation corrosive

Remarks The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Causes serious eye damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Fish toxicity (Components)

Solvent naphtha (petroleum), light arom.

Species rainbow trout (Oncorhynchus mykiss)

LL50 9,2 mg/l

Duration of exposure 96 h

Cyclohexanone

Species Fathead minnow (Pimephales promelas)

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

LC50 630000 µg/l

Daphnia toxicity (Components)

Solvent naphtha (petroleum), light arom.

_LO 3,2 mg/l

Duration of exposure 48 h

Algae toxicity (Components)

Solvent naphtha (petroleum), light arom.

Species Desmodesmus

ErC50 0,42 mg/l

Duration of exposure 72 h

Solvent naphtha (petroleum), light arom.

Species Pseudokirchneriella subcapitata

EC50 0,29 mg/l

Duration of exposure 72 h

Source REACH registration dossier

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label	3	· (\$	3
14.4. Packing group	III	III	III
Remarks	The product is viscous; non-dangerous good in Containers with not more than 450 ltrs.	Transport according to 2.3.2.5 of the IMDG Code	
Limited Quantity	51		
Transport category	3		
14.5. Environmental hazards	-	no	-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

Category 6 Flammable 5.000.000 kg 50.000.000 kg

VOC

VOC (EU) 29,99 %

VOC (EU) 494,8 g/l

Trade name: PLT 2 WHITE 970

Version: 13 / GB Date revised: 17.06.2022

Substance number: 38040057970 Replaces Version: 12 / GB Print date: 17.06.22

Other information

All components are contained in the PICCS inventory. All components are contained in the DSL inventory. All components are contained in the AICS inventory. All components are contained in the ENCS inventory.

All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 4 Acute toxicity, Category 4

Aguatic Chronic 2 Hazardous to the aguatic environment, chronic, Category 2

Asp. Tox. 1

Eye Dam. 1

Flam. Liq. 3

Repr. 2

Resp. Sens. 1

Aspiration hazard, Category 1

Serious eye damage, Category 1

Flammable liquid, Category 3

Reproductive toxicity, Category 2

Respiratory sensitization, Category 1

Skin Irrit. 2 Skin irritation, Category 2
Skin Sens. 1 Skin sensitization, Category 1

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.