

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PLT 55 RICH PALE GOLD 192

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Pad printing ink

Identified Uses

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8a	Transfer of substance or mixture (charging and discharging) at nondedicated facilities
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring
PROC19	Manual activities involving hand contact
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8d	Wide dispersive outdoor use of processing aids in open systems

Uses advised against

SU21 Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

COMEC ITALIA SRL
Piazzale del lavoro 149
21044 Cavarina (VA)
ITALIA
Tel. +39 0331 219516
Fax +39 0331 216161

E-mail address of person responsible for this SDS

info@comec-italia.it
Edgardo Baggini

1.4. Emergency telephone number

CENTRO ANTIVELENI OSPEDALE NIGUARDA MILANO Tel. 02/66101029 (24/24h) - CENTRO ANTIVELENI
POLICLINICO A.GEMELL ROMA Tel. 06/3054343 (24/24h) -

SECTION 2: Hazards identification ***

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Dam. 1	H318
STOT SE 3	H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms ***



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261.9	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains *** Gamma-butyrolactone; Butan-1-ol; n-Butyl acetate

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Pad printing ink based on acrylic resins and on solvents

Hazardous ingredients ***

n-Butyl acetate

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Flam. Liq. 3 H226
STOT SE 3 H336

Hydrocarbons, C11-C12, isoalkanes, <2%.

EINECS no. 918-167-1
Registration no. 01-2119472146-39
Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226
Asp. Tox. 1 H304
Aquatic Chronic 4 H413
EUH066

Butan-1-ol

CAS No. 71-36-3
EINECS no. 200-751-6
Registration no. 01-2119484630-38
Concentration >= 3 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302
STOT SE 3 H335
Skin Irrit. 2 H315
Eye Dam. 1 H318
STOT SE 3 H336
Flam. Liq. 3 H226

Gamma-butyrolactone

CAS No. 96-48-0
EINECS no. 202-509-5
Registration no. 01-2119471839-21
Concentration >= 3 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302
Eye Dam. 1 H318
STOT SE 3 H336

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke; Hydrogen chloride (HCl); Nitrogen oxides (NO_x); Metal oxides

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T4

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Pad printing ink

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Exposure limit values

Butan-1-ol

List	EH40			
Type	WEL			
Short term exposure limit	154	mg/m ³	50	ppm(V)
Skin resorption / sensibilisation: Sk;	Status: 2011			

n-Butyl acetate

List	EH40			
Type	WEL			
Value	724	mg/m ³	150	ppm(V)
Short term exposure limit	966	mg/m ³	200	ppm(V)
Status: 2011				

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Gamma-butyrolactone

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	130	mg/m ³

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	19	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	28	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	8	mg/cm ²

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	8	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Acute	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	340	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Acute	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	958	mg/m ³

Butan-1-ol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	310	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	310	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Concentration	55	mg/m ³
---------------	----	-------------------

Type of value	Derived No Effect Level (DNEL)
Reference group	Consumer
Duration of exposure	Long term
Route of exposure	inhalative
Mode of action	Systemic effects
Concentration	55

mg/m³

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term
Route of exposure	oral
Mode of action	Local effects
Concentration	3,125

mg/kg

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term
Route of exposure	oral
Mode of action	Systemic effects
Concentration	3,125

mg/kg

n-Butyl acetate

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Short term
Route of exposure	inhalative
Mode of action	Systemic effects
Concentration	600

mg/m³

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Short term
Route of exposure	inhalative
Mode of action	Local effects
Concentration	600

mg/m³

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term
Route of exposure	inhalative
Mode of action	Systemic effects
Concentration	300

mg/m³

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term
Route of exposure	inhalative
Mode of action	Local effects
Concentration	300

mg/m³

Type of value	Derived No Effect Level (DNEL)
Reference group	General Population
Duration of exposure	Short term
Route of exposure	inhalative
Mode of action	Systemic effects

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d

Predicted No Effect Concentration (PNEC) *****Gamma-butyrolactone**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,056	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0056	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,56	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,24	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,02	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,014683	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	452	mg/l

Butan-1-ol

Type of value	PNEC	
Type	Freshwater	
Concentration	0,082	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0082	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	2,25	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	2476	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,178	mg/kg

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,0178	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,015	mg/kg

n-Butyl acetate

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,981	mg/kg

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,0981	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l

Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,36	mg/l

8.2. Exposure controls**Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness	>	0,5	mm
--------------------	---	-----	----

Breakthrough time	<	30	min
-------------------	---	----	-----

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	Pasty		
Colour	coloured		
Odour	solvent-like		
Odour threshold			
Remarks	No data available		
pH value			
Remarks	Not applicable		
Melting point			
Remarks	not determined		
Freezing point			
Remarks	not determined		
Initial boiling point and boiling range			
Value	appr. 118	°C	
Pressure	1.013	hPa	
Source	Literature value		
Flash point			
Value	51	°C	
Method	ASTM D 6450 (CCCFP)		
Evaporation rate (ether = 1) :			
Remarks	not determined		
Flammability (solid, gas)			
Not applicable			
Upper/lower flammability or explosive limits			
Lower explosion limit	appr. 0,5	%(V)	
Upper explosion limit	appr. 15,6	%(V)	
Source	Literature value		
Vapour pressure			
Value	appr. 3	hPa	
Temperature	20	°C	
Method	calculated		
Vapour density			
Remarks	not determined		
Density			
Value	1,097	g/cm ³	
Temperature	20	°C	
Method	DIN EN ISO 2811		

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 200 °C

Source Literature value

Efflux time

Value > 150 s

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known

9.2. Other information**Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity**ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)**Acute oral toxicity (Components)****Gamma-butyrolactone**Species rat
LD50 1582 mg/kg
Method OECD 401**Butan-1-ol**Species rat (female)
LD50 2292 mg/kg

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Method OECD 401

n-Butyl acetate

Species rat (female)

LD50 10760 mg/kg

Method OECD 423

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)**n-Butyl acetate**

Species Rats (male/female)

LD50 14112 mg/kg

Method OECD 402

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)**Gamma-butyrolactone**

Species rat

LC0 5,1 mg/l

Duration of exposure 4 h

Administration/Form Vapors

Method OECD 403

n-Butyl acetate

Species Rats (male/female)

LC50 > 21 mg/l

Duration of exposure 4 h

Method OECD 403

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation corrosive

Remarks The classification criteria are met.

Serious eye damage/irritation (Components)**Gamma-butyrolactone**

Species rabbit

evaluation irritant - risk of serious damage to eyes

Method OECD 405

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)**Single exposure**

Remarks The classification criteria are met.

evaluation May cause drowsiness or dizziness.

Repeated exposure

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Remarks

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) (Components)

Gamma-butyrolactone

Single exposure

evaluation

May be irritating to respiratory tract.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Causes serious eye damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks

Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations for the product**

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.




Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Remarks	The product is viscous; non-dangerous good in Containers with not more than 450 ltrs.	Transport according to 2.3.2.5 of the IMDG Code	
Limited Quantity	5 l		
Transport category	3		
14.5. Environmental hazards	-	no	-

Information for all modes of transport**14.6. Special precautions for user**

Transport within the user's premises:

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

Category	6	Flammable	5.000.000	kg	50.000.000	kg
----------	---	-----------	-----------	----	------------	----

VOC ***

VOC (EU)	62,58	%	
VOC (EU)	686,5	g/l	

Other information

All components are contained in the AICS inventory.
All components are contained in the DSL inventory.
All components are contained in the ECL inventory.
All components are contained in the IECSC inventory.
All components are contained in the ENCS inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H413	May cause long lasting harmful effects to aquatic life.

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
Skin Irrit. 2	Skin irritation, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: PLT 55 RICH PALE GOLD 192

Version: 11 / GB

Date revised: 29.04.2022

Substance number: 38170057192

Replaces Version: 10 / GB

Print date: 29.04.22

to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.