

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 1/16 Replaced revision:1 (Dated: 26/03/2024)

# Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**  
Product name  
UFI :

DILUENTE: PLT TEX L,  
P6G3-P049-A00K-4U8N

**1.2. Relevant identified uses of the substance or mixture and uses advised against**  
Intended use  
Screen Printing thinner.

**1.3. Details of the supplier of the safety data sheet**  
Name  
Full address  
District and Country

COMEC ITALIA SRL  
Piazzale del lavoro 149  
21044 Cavarina (VA)  
ITALIA  
  
Tel. +39 0331 219516  
Fax +39 0331 216161  
  
e-mail address of the competent person  
responsible for the Safety Data Sheet  
Supplier:

info@comec-italia.it  
Edgardo Baggini

**1.4. Emergency telephone number**  
For urgent inquiries refer to

Centro Antiveleni di Milano 02 66101029  
(Niguarda Ca Granda - Milano)  
Centro Antiveleni di Pavia 0382 24444  
(Fondazione Maugeri - Pavia)  
Centro Antiveleni di Bergamo 800 883300  
(Papa Giovanni XXIII - Bergamo)  
Centro Antiveleni di Verona 800 011858  
(AOUI - Verona)  
Centro Antiveleni di Firenze 055 7947819  
(Careggi - Firenze)  
Centro Antiveleni di Roma 06 3054343  
(Agostino Gemelli - Roma)  
Centro Antiveleni di Roma 06 49978000  
(Umberto I - Roma)  
Centro Antiveleni di Roma 06 68593726  
(Ospedale pediatrico Bambino Gesù - Roma)  
Centro Antiveleni di Napoli 081 5453333  
(Antonio Cardarelli - Napoli)  
Centro Antiveleni di Foggia 800 183459  
(Azienda ospedaliera universitaria - Foggia)

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

## Printed on 29/07/2024

Page n. 2/16

Replaced revision:1 (Dated: 26/03/2024)

Hazard classification and indication:

H226

## 2.2. Label elements

Hazard pictograms:



### Warning

H226

Precautionary statements:

**P210**

**P280**

Wear protective gloves/ protective clothing / eye protection / face protection.

**P370+P378**

In case of fire: use chemical powder, CO2 or dry send to extinguish.

### 2.3. Other hazards

The product does not contain substances with endocrine disrupting properties in concentration  $\geq 0.1\%$ .

### SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

### 3.2. Mixtures

Contains:

## Identification

**x = Conc. %**

**Classification (EC) 1272/2008 (CLP)**

**DIPROPYLEN GLYCOL  
MONOMETHYL ETHER**

INDEX -

$$82 \leq x < 86$$

Substance with a community workplace exposure limit.

EC 252-104-2

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 3/16 Replaced revision:1 (Dated: 26/03/2024)

CAS 34590-94-8  
REACH Reg. 01-2119450011-60xxxx  
**2-METHOXY-1-METHYLETHYL ACETATE**  
INDEX 607-195-00-7                      15 ≤ x < 16,5                      Flam. Liq. 3 H226, STOT SE 3 H336  
EC 203-603-9  
CAS 108-65-6  
REACH Reg. 01-2119475791-29-xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures**

**4.1. Description of first aid measures**

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:  
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.  
INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.  
EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures**

**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT  
Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.  
UNSUITABLE EXTINGUISHING EQUIPMENT  
Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture**

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE  
Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters**

GENERAL INFORMATION  
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.  
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS  
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 4/16 Replaced revision:1 (Dated: 26/03/2024)

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.  
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.  
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů



	Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg bw/d				
Inhalation			VND	37,2 mg/m3			VND	310 mg/m3
Skin			VND	15 mg/kg bw/d			VND	65 mg/kg bw/d
2-METHOXY-1-METHYLETHYL ACETATE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	275	50	550	100	SKIN		
TLV	CZE	270	49,14	550	100,1	SKIN		
AGW	DEU	270	50	270	50			
MAK	DEU	270	50	270	50			
TLV	DNK	275	50			SKIN	E	
VLA	ESP	275	50	550	100	SKIN		
VLEP	FRA	275	50	550	100	SKIN		
VLEP	ITA	275	50	550	100	SKIN		
TGG	NLD	550						
VLE	PRT	275	50	550	100	SKIN		
NDS/NDSch	POL	260		520		SKIN		
TLV	ROU	275	50	550	100	SKIN		
NGV/KGV	SWE	275	50	550	100	SKIN		
ESD	TUR	275	50	550	100	SKIN		
WEL	GBR	274	50	548	100	SKIN		
OEL	EU	275	50	550	100	SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,635	mg/l			
Normal value in marine water				0,0635	mg/l			
Normal value for fresh water sediment				3,29	mg/kg			
Normal value for marine water sediment				0,329	mg/l			
Normal value for water, intermittent release				6,35	mg/l			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				0,29	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			33 mg/m3	33 mg/m3	550 mg/m3		VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

Legend:

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 7/16 Replaced revision:1 (Dated: 26/03/2024)

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION  
Protect hands with category III work gloves (see standard EN 374).  
The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.  
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION  
Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION  
Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION  
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.  
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.  
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS  
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 8/16 Replaced revision:1 (Dated: 26/03/2024)

Auto-ignition temperature	not available
Decomposition temperature	not available
pH	not available
Kinematic viscosity	not available
Solubility	insoluble in water
Partition coefficient: n-octanol/water	not available
Vapour pressure	21,43 mmHg
Density and/or relative density	0,95
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLEN GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

DIPROPYLEN GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.



COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 9/16 Replaced revision:1 (Dated: 26/03/2024)

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances,strong acids,alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DIPROPYLEN GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat.Possibility of explosion.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances,strong acids,alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.  
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation

COMEC ITALIA SRL	Revision nr. 2
	Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024
	Page n. 10/16
	Replaced revision:1 (Dated: 26/03/2024)

can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

DIPROPYLEN GLYCOL MONOMETHYL ETHER

LD50 (Dermal):	19020 mg/kg Coniglio / Rabbit
LD50 (Oral):	5660 mg/kg Ratto / Rat

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Coniglio / Rabbit
LD50 (Oral):	8500 mg/kg Ratto / Rat
LC50 (Inhalation vapours):	4345 ppm/6h Ratto / Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

DIPROPYLEN GLYCOL MONOMETHYL ETHER	
LC50 - for Fish	> 10000 mg/l/96h Pimephales promelas
EC50 - for Crustacea	1919 mg/l/48h Daphnia Magna
EC10 for Algae / Aquatic Plants	> 969 mg/l/48h
2-METHOXY-1-METHYLETHYL ACETATE	
LC50 - for Fish	134 mg/l/96h Pesce, Oncorhynchus mykiss OECD 203
EC50 - for Crustacea	> 500 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h Selenastrum capricornutum OECD 201

Chronic NOEC for Fish	47,5 mg/l Oryzias latipes 14 gg OECD 204
Chronic NOEC for Crustacea	100 mg/l Daphnia magna 21 gg OECD 202

12.2. Persistence and degradability

DIPROPYLEN GLYCOL MONOMETHYL ETHER	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable OECD 301 F - 75% 10 d - 79% 28 d	
2-METHOXY-1-METHYLETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable OECD GI 301F 83% 10 d	

12.3. Bioaccumulative potential

DIPROPYLEN GLYCOL MONOMETHYL ETHER	
Partition coefficient: n-octanol/water	0,0043
2-METHOXY-1-METHYLETHYL ACETATE	
Partition coefficient: n-octanol/water	1,2
BCF	100

12.4. Mobility in soil

2-METHOXY-1-METHYLETHYL ACETATE	
Partition coefficient: soil/water	1,7

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
Waste transportation may be subject to ADR restrictions.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3272

14.2. UN proper shipping name

ADR / RID: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)  
IMDG: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)  
IATA: ESTERS, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: -		
IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
		Maximum quantity: 220 L	Packaging instructions: 366
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 355
	Pass.:		
	Special provision:	A3	

14.7. Maritime transport in bulk according to IMO instruments

COMEC ITALIA SRL	Revision nr. 2 Dated 07/05/2024
DILUENTE: PLT TEX L,	Printed on 29/07/2024 Page n. 14/16 Replaced revision:1 (Dated: 26/03/2024)

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3

<b>COMEC ITALIA SRL</b>	Revision nr. 2 Dated 07/05/2024
<b>DILUENTE: PLT TEX L,</b>	Printed on 29/07/2024 Page n. 15/16 Replaced revision:1 (Dated: 26/03/2024)

<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H336</b>	May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology

<b>COMEC ITALIA SRL</b>	Revision nr. 2 Dated 07/05/2024
<b>DILUENTE: PLT TEX L,</b>	Printed on 29/07/2024 Page n. 16/16 Replaced revision:1 (Dated: 26/03/2024)

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:  
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.  
This document must not be regarded as a guarantee on any specific product property.  
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**  
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.  
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.  
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:  
The following sections were modified:  
03.