

According to Annex II to REACH - Regulation (EU) 2020/878

### 1.1. Product identifier

PLT 7 WHITE 2: 60 BN,  
G6G2-X0XY-R00X-AKWC

| Intended use | Pad printing ink |
|--------------|------------------|
|--------------|------------------|

|                      |                               |
|----------------------|-------------------------------|
| Name                 | COMEC ITALIA SRL              |
| Full address         | Piazzale del lavoro 149       |
| District and Country | 21044 Cavarina (VA)<br>ITALIA |
|                      | Tel. +39 0331 219516          |
|                      | Fax +39 0331 216161           |

responsible for the Safety Data Sheet      **info@comec-italia.it**  
Supplier:      **Edgardo Baggini**

For urgent inquiries refer to

**Centro Antiveleni di Milano 02 66101029  
(Niguarda Ca Granda - Milano)  
Centro Antiveleni di Pavia 0382 24444  
(Fondazione Maugeri - Pavia)  
Centro Antiveleni di Bergamo 800 883300  
(Papa Giovanni XXIII - Bergamo)  
Centro Antiveleni di Verona 800 011858  
(AOUI - Verona)  
Centro Antiveleni di Firenze 055 7947819  
(Careggi - Firenze)  
Centro Antiveleni di Roma 06 3054343  
(Agostino Gemelli - Roma)  
Centro Antiveleni di Roma 06 49978000  
(Umberto I - Roma)  
Centro Antiveleni di Roma 06 68593726  
(Ospedale pediatrico Bambino Gesù - Roma)  
Centro Antiveleni di Napoli 081 5453333  
(Antonio Cardarelli - Napoli)  
Centro Antiveleni di Foggia 800 183459  
(Azienda ospedaliera universitaria - Foggia)**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and

supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

## 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

### Warning

Hazard statements:

H226

Flammable liquid and vapour.

Precautionary statements:

**P210**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P280**

Wear protective gloves/ protective clothing / eye protection / face protection.

**P370+P378**

In case of fire: use chemical powder, CO2 or dry send to extinguish.

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq 0.1\%$ .

### SECTION 3. Composition/information on ingredients

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer  
Reaction product of BPA; possible contamination <0.05%

### 3.1. Substances

Information not relevant

### 3.2. Mixtures

Contains:

## Identification

**x = Conc. %**

**Classification (EC) 1272/2008 (CLP)**

|                                        |               |                                                                                                                                                                                                                                                                     |
|----------------------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>TITANIUM DIOXIDE</b>                |               |                                                                                                                                                                                                                                                                     |
| INDEX -                                | 45 ≤ x < 47,5 |                                                                                                                                                                                                                                                                     |
| EC 236-675-5                           |               |                                                                                                                                                                                                                                                                     |
| CAS 13463-67-7                         |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 01-2119489379-17-0018       |               |                                                                                                                                                                                                                                                                     |
| <b>BUTYLGLYCOL ACETATE</b>             |               |                                                                                                                                                                                                                                                                     |
| INDEX 607-038-00-2                     | 12 ≤ x < 13,5 | Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332                                                                                                                                                                                                             |
| EC 203-933-3                           |               | ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l                                                                                                                                                                                        |
| CAS 112-07-2                           |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 01-2119475112-47xxxx        |               |                                                                                                                                                                                                                                                                     |
| <b>2-METHOXY-1-METHYLETHYL ACETATE</b> |               |                                                                                                                                                                                                                                                                     |
| INDEX 607-195-00-7                     | 4,5 ≤ x < 5   | Flam. Liq. 3 H226, STOT SE 3 H336                                                                                                                                                                                                                                   |
| EC 203-603-9                           |               |                                                                                                                                                                                                                                                                     |
| CAS 108-65-6                           |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 01-2119475791-29-xxxx       |               |                                                                                                                                                                                                                                                                     |
| <b>XYLENE</b>                          |               |                                                                                                                                                                                                                                                                     |
| INDEX 601-022-00-9                     | 3,5 ≤ x < 4   | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C<br>ATE Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11,58 mg/l/4h |
| EC 215-535-7                           |               |                                                                                                                                                                                                                                                                     |
| CAS 1330-20-7                          |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 01-2119488216-32-xxxx       |               |                                                                                                                                                                                                                                                                     |
| <b>ETHYLBENZENE</b>                    |               |                                                                                                                                                                                                                                                                     |
| INDEX 601-023-00-4                     | 0,9 ≤ x < 1   | Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412<br>LC50 Inhalation vapours: 17,2 mg/l/4h                                                                                                                             |
| EC 202-849-4                           |               |                                                                                                                                                                                                                                                                     |
| CAS 100-41-4                           |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 01-2119489370-35-xxxx       |               |                                                                                                                                                                                                                                                                     |
| <b>4,4'-ISOPROPYLIDENEDIPHENOL</b>     |               |                                                                                                                                                                                                                                                                     |
| INDEX 604-030-00-0                     | 0 < x < 0,01  | Repr. 1B H360F, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=10                                                                                                                                           |
| EC 201-245-8                           |               |                                                                                                                                                                                                                                                                     |
| CAS 80-05-7                            |               |                                                                                                                                                                                                                                                                     |
| REACH Reg. 2119457856-23-xxxx          |               |                                                                                                                                                                                                                                                                     |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.  
In case of doubt or in the presence of symptoms contact a doctor and show him this document.  
In case of more severe symptoms, ask for immediate medical aid.  
EYES: Wash immediately and thoroughly with running water. Get medical advice if you feel symptoms.  
SKIN: Wash with plenty of water. Get medical advice if you feel symptoms.  
INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical

|                       |                                                                                  |
|-----------------------|----------------------------------------------------------------------------------|
| COMEC ITALIA SRL      | Revision nr. 4<br>Dated 03/03/2025                                               |
| PLT 7 WHITE 2: 60 BN, | Printed on 03/03/2025<br>Page n. 4/22<br>Replaced revision:3 (Dated: 07/03/2024) |

advice.  
INHALATION: Remove to open air. Get medical advice if you feel symptoms.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.  
  
DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.  
  
Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT  
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.  
UNSUITABLE EXTINGUISHING EQUIPMENT  
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE  
Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION  
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.  
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS  
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.  
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any

|                       |                                                                                  |
|-----------------------|----------------------------------------------------------------------------------|
| COMEC ITALIA SRL      | Revision nr. 4<br>Dated 03/03/2025                                               |
| PLT 7 WHITE 2: 60 BN, | Printed on 03/03/2025<br>Page n. 5/22<br>Replaced revision:3 (Dated: 07/03/2024) |

contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

2-METHOXY-1-METHYLETHYL ACETATE

Store in an inert atmosphere, sheletered from moisture because it hydrolises easily.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

|     |                 |                                                                                                                                                                |
|-----|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BGR | България        | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci                      |
| DEU | Deutschland     | Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58                  |
| DNK | Danmark         | Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019                                                                          |
| ESP | España          | Límites de exposición profesional para agentes químicos en España 2023                                                                                         |
| FRA | France          | Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021                                             |



| Threshold Limit Value                                 |         |                      |                |               |                    |                        |                |               |                  |  |  |
|-------------------------------------------------------|---------|----------------------|----------------|---------------|--------------------|------------------------|----------------|---------------|------------------|--|--|
| Type                                                  | Country | TWA/8h               |                | STEL/15min    |                    | Remarks / Observations |                |               |                  |  |  |
|                                                       |         | mg/m3                | ppm            | mg/m3         | ppm                |                        |                |               |                  |  |  |
| TLV                                                   | BGR     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| TLV                                                   | CZE     | 130                  | 19,5           | 300           | 45                 | SKIN                   |                |               |                  |  |  |
| AGW                                                   | DEU     | 65                   | 10             | 130           | 20                 | SKIN                   | 11             |               |                  |  |  |
| MAK                                                   | DEU     | 66                   | 10             | 132           | 20                 | SKIN                   | Hinweis        |               |                  |  |  |
| TLV                                                   | DNK     | 134                  | 20             | 333           | 50                 | SKIN                   | E              |               |                  |  |  |
| VLA                                                   | ESP     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| VLEP                                                  | FRA     | 66,5                 | 10             | 333           | 50                 |                        |                |               |                  |  |  |
| VLEP                                                  | ITA     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| TGG                                                   | NLD     | 135                  |                | 333           |                    | SKIN                   |                |               |                  |  |  |
| VLE                                                   | PRT     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| NDS/NDSch                                             | POL     | 100                  |                | 300           |                    | SKIN                   |                |               |                  |  |  |
| TLV                                                   | ROU     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| NGV/KGV                                               | SWE     | 70                   | 10             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| ESD                                                   | TUR     | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| WEL                                                   | GBR     | 133                  | 20             | 332           | 50                 | SKIN                   |                |               |                  |  |  |
| OEL                                                   | EU      | 133                  | 20             | 333           | 50                 | SKIN                   |                |               |                  |  |  |
| TLV-ACGIH                                             |         | 131                  | 20             |               |                    |                        |                |               |                  |  |  |
| Predicted no-effect concentration - PNEC              |         |                      |                |               |                    |                        |                |               |                  |  |  |
| Normal value in fresh water                           |         |                      |                | 0,304         | mg/l               |                        |                |               |                  |  |  |
| Normal value in marine water                          |         |                      |                | 0,03          | mg/l               |                        |                |               |                  |  |  |
| Normal value for fresh water sediment                 |         |                      |                | 2,03          | mg/l               |                        |                |               |                  |  |  |
| Normal value for marine water sediment                |         |                      |                | 0,203         | mg/l               |                        |                |               |                  |  |  |
| Normal value for water, intermittent release          |         |                      |                | 0,56          | mg/l               |                        |                |               |                  |  |  |
| Normal value of STP microorganisms                    |         |                      |                | 90            | mg/l               |                        |                |               |                  |  |  |
| Normal value for the food chain (secondary poisoning) |         |                      |                | 60            | mg/kg              |                        |                |               |                  |  |  |
| Normal value for the terrestrial compartment          |         |                      |                | 0,415         | mg/kg/d            |                        |                |               |                  |  |  |
| Health - Derived no-effect level - DNEL / DMEL        |         |                      |                |               |                    |                        |                |               |                  |  |  |
|                                                       |         | Effects on consumers |                |               | Effects on workers |                        |                |               |                  |  |  |
| Route of exposure                                     |         | Acute local          | Acute systemic | Chronic local | Chronic systemic   | Acute local            | Acute systemic | Chronic local | Chronic systemic |  |  |
| Oral                                                  | VND     |                      | 36 mg/kg/d     | VND           | 4,3 mg/kg/d        |                        |                |               |                  |  |  |
| Inhalation                                            |         | 200 mg/m3            | 499 mg/m3      | VND           | 80 mg/m3           | 333 mg/m3              | 773 mg/m3      | VND           | 133 mg/m3        |  |  |
| Skin                                                  |         |                      | 72 mg/kg bw/d  | VND           | 102 mg/kg/d        | 102 mg/kg/d            | 27 mg/kg/d     | VND           | 169 mg/kg/d      |  |  |
| 2-METHOXY-1-METHYLETHYL ACETATE                       |         |                      |                |               |                    |                        |                |               |                  |  |  |
| Threshold Limit Value                                 |         |                      |                |               |                    |                        |                |               |                  |  |  |
| Type                                                  | Country | TWA/8h               |                | STEL/15min    |                    | Remarks / Observations |                |               |                  |  |  |
|                                                       |         | mg/m3                | ppm            | mg/m3         | ppm                |                        |                |               |                  |  |  |
| TLV                                                   | BGR     | 275                  | 50             | 550           | 100                | SKIN                   |                |               |                  |  |  |
| TLV                                                   | CZE     | 270                  | 49,14          | 550           | 100,1              | SKIN                   |                |               |                  |  |  |
| AGW                                                   | DEU     | 270                  | 50             | 270           | 50                 |                        |                |               |                  |  |  |
| MAK                                                   | DEU     | 270                  | 50             | 270           | 50                 |                        |                |               |                  |  |  |
| TLV                                                   | DNK     | 275                  | 50             | 550           | 100                | SKIN                   | E              |               |                  |  |  |

|                                                |             |                      |               |                  |                    |                                         |               |                  |
|------------------------------------------------|-------------|----------------------|---------------|------------------|--------------------|-----------------------------------------|---------------|------------------|
| COMEC ITALIA SRL                               |             |                      |               |                  |                    | Revision nr. 4                          |               |                  |
| PLT 7 WHITE 2: 60 BN,                          |             |                      |               |                  |                    | Dated 03/03/2025                        |               |                  |
|                                                |             |                      |               |                  |                    | Printed on 03/03/2025                   |               |                  |
|                                                |             |                      |               |                  |                    | Page n. 8/22                            |               |                  |
|                                                |             |                      |               |                  |                    | Replaced revision:3 (Dated: 07/03/2024) |               |                  |
|                                                |             |                      |               |                  |                    |                                         |               |                  |
| VLA                                            | ESP         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| VLEP                                           | FRA         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| VLEP                                           | ITA         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| TGG                                            | NLD         | 550                  |               |                  |                    |                                         |               |                  |
| VLE                                            | PRT         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| NDS/NDSch                                      | POL         | 260                  |               | 520              |                    | SKIN                                    |               |                  |
| TLV                                            | ROU         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| NGV/KGV                                        | SWE         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| ESD                                            | TUR         | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| WEL                                            | GBR         | 274                  | 50            | 548              | 100                | SKIN                                    |               |                  |
| OEL                                            | EU          | 275                  | 50            | 550              | 100                | SKIN                                    |               |                  |
| Predicted no-effect concentration - PNEC       |             |                      |               |                  |                    |                                         |               |                  |
| Normal value in fresh water                    |             |                      |               | 0,635            | mg/l               |                                         |               |                  |
| Normal value in marine water                   |             |                      |               | 0,0635           | mg/l               |                                         |               |                  |
| Normal value for fresh water sediment          |             |                      |               | 3,29             | mg/kg              |                                         |               |                  |
| Normal value for marine water sediment         |             |                      |               | 0,329            | mg/l               |                                         |               |                  |
| Normal value for water, intermittent release   |             |                      |               | 6,35             | mg/l               |                                         |               |                  |
| Normal value of STP microorganisms             |             |                      |               | 100              | mg/l               |                                         |               |                  |
| Normal value for the terrestrial compartment   |             |                      |               | 0,29             | mg/kg              |                                         |               |                  |
| Health - Derived no-effect level - DNEL / DMEL |             |                      |               |                  |                    |                                         |               |                  |
|                                                |             | Effects on consumers |               |                  | Effects on workers |                                         |               |                  |
| Route of exposure                              | Acute local | Acute systemic       | Chronic local | Chronic systemic | Acute local        | Acute systemic                          | Chronic local | Chronic systemic |
| Oral                                           |             |                      | VND           | 1,67 mg/kg       |                    |                                         |               |                  |
| Inhalation                                     |             |                      | 33 mg/m3      | 33 mg/m3         | 550 mg/m3          |                                         | VND           | 275 mg/m3        |
| Skin                                           |             |                      | VND           | 54,8 mg/kg       |                    |                                         | VND           | 153,5 mg/kg      |
| XYLENE                                         |             |                      |               |                  |                    |                                         |               |                  |
| Threshold Limit Value                          |             |                      |               |                  |                    |                                         |               |                  |
| Type                                           | Country     | TWA/8h               |               | STEL/15min       |                    | Remarks / Observations                  |               |                  |
|                                                |             | mg/m3                | ppm           | mg/m3            | ppm                |                                         |               |                  |
| TLV                                            | BGR         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| TLV                                            | CZE         | 200                  | 45,4          | 400              | 90,8               | SKIN                                    |               |                  |
| AGW                                            | DEU         | 220                  | 50            | 440              | 100                | SKIN                                    |               |                  |
| MAK                                            | DEU         | 220                  | 50            | 440              | 100                | SKIN                                    |               |                  |
| TLV                                            | DNK         | 109                  | 25            |                  |                    | SKIN                                    |               | E                |
| VLA                                            | ESP         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| VLEP                                           | FRA         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| AK                                             | HUN         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| VLEP                                           | ITA         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| TGG                                            | NLD         | 210                  |               | 442              |                    | SKIN                                    |               |                  |
| VLE                                            | PRT         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
| NDS/NDSch                                      | POL         | 100                  |               | 200              |                    | SKIN                                    |               |                  |
| TLV                                            | ROU         | 221                  | 50            | 442              | 100                | SKIN                                    |               |                  |
|                                                |             |                      |               |                  |                    |                                         |               |                  |

|                                                |             |                      |               |                  |                        |                                         |               |                  |
|------------------------------------------------|-------------|----------------------|---------------|------------------|------------------------|-----------------------------------------|---------------|------------------|
| COMEC ITALIA SRL                               |             |                      |               |                  |                        | Revision nr. 4                          |               |                  |
| PLT 7 WHITE 2: 60 BN,                          |             |                      |               |                  |                        | Dated 03/03/2025                        |               |                  |
|                                                |             |                      |               |                  |                        | Printed on 03/03/2025                   |               |                  |
|                                                |             |                      |               |                  |                        | Page n. 9/22                            |               |                  |
|                                                |             |                      |               |                  |                        | Replaced revision:3 (Dated: 07/03/2024) |               |                  |
|                                                |             |                      |               |                  |                        |                                         |               |                  |
| NGV/KGV                                        | SWE         | 221                  | 50            | 442              | 100                    | SKIN                                    |               |                  |
| ESD                                            | TUR         | 221                  | 50            | 442              | 100                    | SKIN                                    |               |                  |
| WEL                                            | GBR         | 220                  | 50            | 441              | 100                    | SKIN                                    |               |                  |
| OEL                                            | EU          | 221                  | 50            | 442              | 100                    | SKIN                                    |               |                  |
| TLV-ACGIH                                      |             |                      | 20            |                  |                        |                                         |               |                  |
| Predicted no-effect concentration - PNEC       |             |                      |               |                  |                        |                                         |               |                  |
| Normal value in fresh water                    |             |                      |               | 0,327            |                        | mg/l                                    |               |                  |
| Normal value in marine water                   |             |                      |               | 0,327            |                        | mg/l                                    |               |                  |
| Normal value for fresh water sediment          |             |                      |               | 12,46            |                        | mg/kg                                   |               |                  |
| Normal value for marine water sediment         |             |                      |               | 12,46            |                        | mg/kg                                   |               |                  |
| Normal value for water, intermittent release   |             |                      |               | 0,327            |                        | mg/l                                    |               |                  |
| Normal value of STP microorganisms             |             |                      |               | 6,58             |                        | mg/l                                    |               |                  |
| Normal value for the terrestrial compartment   |             |                      |               | 2,31             |                        | mg/kg                                   |               |                  |
| Health - Derived no-effect level - DNEL / DMEL |             |                      |               |                  |                        |                                         |               |                  |
|                                                |             | Effects on consumers |               |                  | Effects on workers     |                                         |               |                  |
| Route of exposure                              | Acute local | Acute systemic       | Chronic local | Chronic systemic | Acute local            | Acute systemic                          | Chronic local | Chronic systemic |
| Oral                                           |             |                      | VND           | 1,6 mg/kg/d      |                        |                                         |               |                  |
| Inhalation                                     | 174 mg/m3   | 174 mg/m3            | VND           | 14,8 mg/m3       | 289 mg/m3              | 289 mg/m3                               | 77 mg/m3      | 77 mg/m3         |
| Skin                                           |             |                      | VND           | 108 mg/kg/d      | 174 mg/m3              | VND                                     | VND           | 180 mg/kg        |
| ETHYLBENZENE                                   |             |                      |               |                  |                        |                                         |               |                  |
| Threshold Limit Value                          |             |                      |               |                  |                        |                                         |               |                  |
| Type                                           | Country     | TWA/8h               | STEL/15min    |                  | Remarks / Observations |                                         |               |                  |
|                                                |             | mg/m3                | ppm           | mg/m3            | ppm                    |                                         |               |                  |
| TLV                                            | BGR         | 435                  |               | 545              |                        | SKIN                                    |               |                  |
| TLV                                            | CZE         | 200                  | 45,4          | 500              | 113,5                  | SKIN                                    |               |                  |
| AGW                                            | DEU         | 88                   | 20            | 176              | 40                     | SKIN                                    |               |                  |
| MAK                                            | DEU         | 88                   | 20            | 176              | 40                     | SKIN                                    |               |                  |
| TLV                                            | DNK         | 217                  | 50            | 434              | 100                    | SKIN E                                  |               |                  |
| VLA                                            | ESP         | 441                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| VLEP                                           | FRA         | 88,4                 | 20            | 442              | 100                    | SKIN                                    |               |                  |
| AK                                             | HUN         | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| VLEP                                           | ITA         | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| TGG                                            | NLD         | 215                  |               | 430              |                        | SKIN                                    |               |                  |
| VLE                                            | PRT         | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| NDS/NDSch                                      | POL         | 200                  |               | 400              |                        | SKIN                                    |               |                  |
| TLV                                            | ROU         | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| NGV/KGV                                        | SWE         | 220                  | 50            | 884              | 200                    | SKIN                                    |               |                  |
| ESD                                            | TUR         | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| WEL                                            | GBR         | 441                  | 100           | 552              | 125                    | SKIN                                    |               |                  |
| OEL                                            | EU          | 442                  | 100           | 884              | 200                    | SKIN                                    |               |                  |
| TLV-ACGIH                                      |             | 87                   | 20            |                  |                        |                                         |               |                  |
| Predicted no-effect concentration - PNEC       |             |                      |               |                  |                        |                                         |               |                  |
| Normal value in fresh water                    |             |                      |               | 0,1              |                        | mg/l ECHA 2018                          |               |                  |
|                                                |             |                      |               |                  |                        |                                         |               |                  |

|                                                       |      |                 |
|-------------------------------------------------------|------|-----------------|
| Normal value in marine water                          | 0,01 | mg/l ECHA 2018  |
| Normal value for fresh water sediment                 | 13,7 | mg/kg ECHA 2018 |
| Normal value for marine water sediment                | 1,37 | mg/kg ECHA 2018 |
| Normal value for water, intermittent release          | 0,1  | mg/l ECHA 2018  |
| Normal value of STP microorganisms                    | 9,6  | mg/l ECHA 2018  |
| Normal value for the food chain (secondary poisoning) | 20   | mg/kg ECHA 2018 |
| Normal value for the terrestrial compartment          | 2,68 | mg/kg ECHA 2018 |

| 4,4'-ISOPROPYLIDENEDIPHENOL                  |         |        |            |       |                        |
|----------------------------------------------|---------|--------|------------|-------|------------------------|
| Threshold Limit Value                        |         |        |            |       |                        |
| Type                                         | Country | TWA/8h | STEL/15min |       | Remarks / Observations |
|                                              |         | mg/m3  | ppm        | mg/m3 | ppm                    |
| TLV                                          | BGR     | 2      |            |       | INHAL                  |
| TLV                                          | CZE     | 2      |            | 5     | INHAL                  |
| AGW                                          | DEU     | 5      |            | 5     | INHAL                  |
| MAK                                          | DEU     | 5      |            | 5     | INHAL                  |
| TLV                                          | DNK     | 2      |            |       | E                      |
| VLA                                          | ESP     | 2      |            |       |                        |
| VLEP                                         | FRA     | 2      |            |       |                        |
| AK                                           | HUN     | 2      |            |       |                        |
| VLEP                                         | ITA     | 10     |            |       | INHAL                  |
| TGG                                          | NLD     | 2      |            |       | INHAL                  |
| VLE                                          | PRT     | 2      |            |       | INHAL                  |
| NDS/NDSch                                    | POL     | 2      |            |       | INHAL                  |
| TLV                                          | ROU     | 2      |            |       | INHAL                  |
| WEL                                          | GBR     | 2      |            |       |                        |
| OEL                                          | EU      | 2      |            |       | INHAL                  |
| Predicted no-effect concentration - PNEC     |         |        |            |       |                        |
| Normal value in fresh water                  |         |        |            | 0,018 | mg/l                   |
| Normal value in marine water                 |         |        |            | 0,016 | mg/l                   |
| Normal value of STP microorganisms           |         |        |            | 320   | mg/l                   |
| Normal value for the terrestrial compartment |         |        |            | 3,7   | mg/kg                  |

| Health - Derived no-effect level - DNEL / DMEL |                      |                |               |                  |                    |                 |               |                  |
|------------------------------------------------|----------------------|----------------|---------------|------------------|--------------------|-----------------|---------------|------------------|
| Route of exposure                              | Effects on consumers |                |               |                  | Effects on workers |                 |               |                  |
|                                                | Acute local          | Acute systemic | Chronic local | Chronic systemic | Acute local        | Acute systemic  | Chronic local | Chronic systemic |
| Oral                                           |                      |                |               |                  |                    | 0,05 mg/kg bw/d |               | 0,05 mg/kg bw/d  |
| Inhalation                                     | 5 mg/m3              | 5 mg/m3        | 5 mg/m3       | 0,25 mg/m3       |                    | 10 mg/m3        |               | 10 mg/m3         |
| Skin                                           |                      | 0,7 mg/kg bw/d |               | 0,7 mg/kg bw/d   |                    | 1,4 mg/kg bw/d  |               | 1,4 mg/kg bw/d   |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.  
The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.  
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties                     | Value              | Information |
|--------------------------------|--------------------|-------------|
| Appearance                     | liquid             |             |
| Colour                         | various            |             |
| Odour                          | typical of solvent |             |
| Melting point / freezing point | not available      |             |
| Initial boiling point          | not available      |             |
| Flammability                   | not available      |             |
| Lower explosive limit          | not available      |             |
| Upper explosive limit          | not available      |             |
| Flash point                    | 23 ≤ T ≤ 60 °C     |             |
| Auto-ignition temperature      | not available      |             |

|                                        |                |
|----------------------------------------|----------------|
| Decomposition temperature              | not available  |
| pH                                     | not available  |
| Kinematic viscosity                    | not available  |
| Solubility                             | not available  |
| Partition coefficient: n-octanol/water | not available  |
| Vapour pressure                        | not available  |
| Density and/or relative density        | not available  |
| Relative vapour density                | not available  |
| Particle characteristics               | not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances,strong acids,alkaline metals.

XYLENE

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

|                       |                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------|
| COMEC ITALIA SRL      | Revision nr. 4<br>Dated 03/03/2025                                                |
| PLT 7 WHITE 2: 60 BN, | Printed on 03/03/2025<br>Page n. 13/22<br>Replaced revision:3 (Dated: 07/03/2024) |

ETHYLBENZENE

Reacts violently with: strong oxidants.Attacks various types of plastic materials.May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances,strong acids,alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane,styrene,hydrogen,ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.  
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation

|                       |                                         |
|-----------------------|-----------------------------------------|
| COMEC ITALIA SRL      | Revision nr. 4                          |
|                       | Dated 03/03/2025                        |
| PLT 7 WHITE 2: 60 BN, | Printed on 03/03/2025                   |
|                       | Page n. 14/22                           |
|                       | Replaced revision:3 (Dated: 07/03/2024) |

can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

XYLENE

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

|                                            |             |
|--------------------------------------------|-------------|
| ATE (Inhalation - vapours) of the mixture: | > 20 mg/l   |
| ATE (Oral) of the mixture:                 | >2000 mg/kg |
| ATE (Dermal) of the mixture:               | >2000 mg/kg |

TITANIUM DIOXIDE

|                                  |                       |
|----------------------------------|-----------------------|
| LD50 (Oral):                     | > 5000 mg/l Ratto/Rat |
| LC50 (Inhalation mists/powders): | > 6,82 mg/l Ratto/Rat |

polyester polyol

|              |                          |
|--------------|--------------------------|
| LD50 (Oral): | > 2000 mg/kg Ratto / Rat |
|--------------|--------------------------|

BUTYLGLYCOL ACETATE

|                            |                                                                                                                                           |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| ATE (Dermal):              | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP<br>(figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Oral):                | 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP<br>(figure used for calculation of the acute toxicity estimate of the mixture)  |
| LC50 (Inhalation vapours): | > 2,66 mg/l/4h Rat                                                                                                                        |
| ATE (Inhalation vapours):  | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP<br>(figure used for calculation of the acute toxicity estimate of the mixture)    |

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer

|                |                          |
|----------------|--------------------------|
| LD50 (Dermal): | > 2000 mg/kg Ratto / Rat |
| LD50 (Oral):   | > 2000 mg/kg Ratto / Rat |

2-METHOXY-1-METHYLETHYL ACETATE

|                            |                                |
|----------------------------|--------------------------------|
| LD50 (Dermal):             | > 5000 mg/kg Coniglio / Rabbit |
| LD50 (Oral):               | 8500 mg/kg Ratto / Rat         |
| LC50 (Inhalation vapours): | 4345 ppm/6h Ratto / Rat        |

XYLENE

|                            |                                                                                                                                           |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 (Dermal):             | 4350 mg/kg Rabbit                                                                                                                         |
| ATE (Dermal):              | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP<br>(figure used for calculation of the acute toxicity estimate of the mixture) |
| LD50 (Oral):               | 3523 mg/kg Rat                                                                                                                            |
| LC50 (Inhalation vapours): | 11,58 mg/l/4h Rat                                                                                                                         |

ETHYLBENZENE

|                |                    |
|----------------|--------------------|
| LD50 (Dermal): | 15354 mg/kg Rabbit |
| LD50 (Oral):   | 3500 mg/kg Rat     |

|                                                                                                                                                                                                   |  |                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------------------|
| COMEC ITALIA SRL                                                                                                                                                                                  |  | Revision nr. 4                          |
|                                                                                                                                                                                                   |  | Dated 03/03/2025                        |
| PLT 7 WHITE 2: 60 BN,                                                                                                                                                                             |  | Printed on 03/03/2025                   |
|                                                                                                                                                                                                   |  | Page n. 15/22                           |
|                                                                                                                                                                                                   |  | Replaced revision:3 (Dated: 07/03/2024) |
| LC50 (Inhalation vapours): 17,2 mg/l/4h Rat                                                                                                                                                       |  |                                         |
| 4,4'-ISOPROPYLIDENEDIPHENOL                                                                                                                                                                       |  |                                         |
| LD50 (Dermal):                                                                                                                                                                                    |  | 3000 mg/kg Rabbit                       |
| LD50 (Oral):                                                                                                                                                                                      |  | 5000 mg/kg                              |
| <u>SKIN CORROSION / IRRITATION</u>                                                                                                                                                                |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>SERIOUS EYE DAMAGE / IRRITATION</u>                                                                                                                                                            |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>RESPIRATORY OR SKIN SENSITISATION</u>                                                                                                                                                          |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>GERM CELL MUTAGENICITY</u>                                                                                                                                                                     |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>CARCINOGENICITY</u>                                                                                                                                                                            |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| XYLENE                                                                                                                                                                                            |  |                                         |
| Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).                                                                         |  |                                         |
| The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".                                                               |  |                                         |
| ETHYLBENZENE                                                                                                                                                                                      |  |                                         |
| Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).                                                                      |  |                                         |
| Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).                                                      |  |                                         |
| <u>REPRODUCTIVE TOXICITY</u>                                                                                                                                                                      |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>STOT - SINGLE EXPOSURE</u>                                                                                                                                                                     |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>STOT - REPEATED EXPOSURE</u>                                                                                                                                                                   |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <u>ASPIRATION HAZARD</u>                                                                                                                                                                          |  |                                         |
| Does not meet the classification criteria for this hazard class                                                                                                                                   |  |                                         |
| <b>11.2. Information on other hazards</b>                                                                                                                                                         |  |                                         |
| Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation. |  |                                         |

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

|                                   |                                                       |
|-----------------------------------|-------------------------------------------------------|
| polyester polyol                  |                                                       |
| LC50 - for Fish                   | > 100 mg/l/96h Danio rerio                            |
| EC50 - for Crustacea              | > 100 mg/l/48h Daphnia magna                          |
| TITANIUM DIOXIDE                  |                                                       |
| LC50 - for Fish                   | > 10000 mg/l/96h Cypridonon variegatus                |
| 2-METHOXY-1-METHYLETHYL ACETATE   |                                                       |
| LC50 - for Fish                   | 134 mg/l/96h Pesce, Oncorhynchus mykiss OECD 203      |
| EC50 - for Crustacea              | > 500 mg/l/48h Daphnia magna                          |
| EC50 - for Algae / Aquatic Plants | > 1000 mg/l/72h Selenastrum capricornutum OECD 201    |
| Chronic NOEC for Fish             | 47,5 mg/l Oryzias latipes 14 gg OECD 204              |
| Chronic NOEC for Crustacea        | 100 mg/l Dapnia magna 21 gg OECD 202                  |
| ETHYLBENZENE                      |                                                       |
| LC50 - for Fish                   | 4,2 mg/l/96h Oncorhynchus mykiss OECD TG 203          |
| EC50 - for Crustacea              | 2,4 mg/l/48h Daphnia magna (database Ecotox)          |
| EC50 - for Algae / Aquatic Plants | 3,6 mg/l/72h Pseudokirchneriella subcapitata (IUCLID) |
| BUTYLGLYCOL ACETATE               |                                                       |
| LC50 - for Fish                   | > 20 mg/l/96h Fish 20-40 mg/kg (48h)                  |
| EC50 - for Crustacea              | 145 mg/l/24h Daphnia Magna (24h)                      |
| EC50 - for Algae / Aquatic Plants | 1570 mg/l/72h Scenedesmus subspicatus                 |
| 4,4'-ISOPROPYLIDENEDIPHENOL       |                                                       |
| LC50 - for Fish                   | 9,4 mg/l/96h Menidia menidia                          |
| EC50 - for Crustacea              | 10,2 mg/l/48h Daphnia magna                           |
| Chronic NOEC for Fish             | 0,016 mg/l Pimephales promelas                        |
| Chronic NOEC for Crustacea        | 1,8 mg/l Daphnia magna                                |

12.2. Persistence and degradability

|                                 |                 |
|---------------------------------|-----------------|
| polyester polyol                |                 |
| NOT rapidly degradable          |                 |
| XYLENE                          |                 |
| Solubility in water             | 100 - 1000 mg/l |
| Rapidly degradable              |                 |
| 2-METHOXY-1-METHYLETHYL ACETATE |                 |
| Solubility in water             | > 10000 mg/l    |
| Rapidly degradable              |                 |

|                                                                                                         |            |                                         |
|---------------------------------------------------------------------------------------------------------|------------|-----------------------------------------|
| COMEC ITALIA SRL                                                                                        |            | Revision nr. 4                          |
|                                                                                                         |            | Dated 03/03/2025                        |
| PLT 7 WHITE 2: 60 BN,                                                                                   |            | Printed on 03/03/2025                   |
|                                                                                                         |            | Page n. 17/22                           |
|                                                                                                         |            | Replaced revision:3 (Dated: 07/03/2024) |
| OECD GI 301F 83% 10 d                                                                                   |            |                                         |
| ETHYLBENZENE                                                                                            |            |                                         |
| Solubility in water                                                                                     | 200 mg/l   | ECHA 2018/05/18                         |
| Rapidly degradable                                                                                      |            |                                         |
| BUTYLGLYCOL ACETATE                                                                                     |            |                                         |
| Solubility in water                                                                                     | 15000 mg/l |                                         |
| Rapidly degradable                                                                                      |            |                                         |
| 4,4'-ISOPROPYLIDENEDIPHENOL                                                                             |            |                                         |
| Solubility in water                                                                                     | 301 mg/l   |                                         |
| Rapidly degradable                                                                                      |            |                                         |
| 12.3. Bioaccumulative potential                                                                         |            |                                         |
| XYLENE                                                                                                  |            |                                         |
| Partition coefficient: n-octanol/water                                                                  | 3,12       |                                         |
| BCF                                                                                                     | 25,9       |                                         |
| 2-METHOXY-1-METHYLETHYL ACETATE                                                                         |            |                                         |
| Partition coefficient: n-octanol/water                                                                  | 1,2        |                                         |
| BCF                                                                                                     | 100        |                                         |
| ETHYLBENZENE                                                                                            |            |                                         |
| Partition coefficient: n-octanol/water                                                                  | 3,6        |                                         |
| BUTYLGLYCOL ACETATE                                                                                     |            |                                         |
| Partition coefficient: n-octanol/water                                                                  | 1,51       |                                         |
| 4,4'-ISOPROPYLIDENEDIPHENOL                                                                             |            |                                         |
| Partition coefficient: n-octanol/water                                                                  | 3,4        |                                         |
| BCF                                                                                                     | 73         |                                         |
| 12.4. Mobility in soil                                                                                  |            |                                         |
| XYLENE                                                                                                  |            |                                         |
| Partition coefficient: soil/water                                                                       | 2,73       |                                         |
| 2-METHOXY-1-METHYLETHYL ACETATE                                                                         |            |                                         |
| Partition coefficient: soil/water                                                                       | 1,7        |                                         |
| 4,4'-ISOPROPYLIDENEDIPHENOL                                                                             |            |                                         |
| Partition coefficient: soil/water                                                                       | 2,95       |                                         |
| 12.5. Results of PBT and vPvB assessment                                                                |            |                                         |
| On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%. |            |                                         |
| 12.6. Endocrine disrupting properties                                                                   |            |                                         |

|                       |                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------|
| COMEC ITALIA SRL      | Revision nr. 4<br>Dated 03/03/2025                                                |
| PLT 7 WHITE 2: 60 BN, | Printed on 03/03/2025<br>Page n. 18/22<br>Replaced revision:3 (Dated: 07/03/2024) |

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
Waste transportation may be subject to ADR restrictions.  
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1210

14.2. UN proper shipping name

ADR / RID: PRINTING INK or PRINTING INK RELATED MATERIAL  
IMDG: PRINTING INK or PRINTING INK RELATED MATERIAL  
IATA: PRINTING INK or PRINTING INK RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO  
IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

|            |                                              |                          |                                |
|------------|----------------------------------------------|--------------------------|--------------------------------|
| ADR / RID: | HIN - Kemler: 30                             | Limited Quantities: 5 It | Tunnel restriction code: (D/E) |
| IMDG:      | Special provision: 163, 367<br>EMS: F-E, S-D | Limited Quantities: 5 It |                                |
| IATA:      | Cargo:                                       | Maximum quantity: 220 L  | Packaging instructions: 366    |
|            | Passengers:                                  | Maximum quantity: 60 L   | Packaging instructions: 355    |
|            | Special provision:                           | A3, A72, A192            |                                |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

|                     |        |                                                               |
|---------------------|--------|---------------------------------------------------------------|
| Product             |        |                                                               |
| Point               | 3 - 40 |                                                               |
| Contained substance |        |                                                               |
| Point               | 75     | 4,4'-ISOPROPYLIDENEDIPHENOL<br>REACH Reg.: 2119457856-23-xxxx |
| Point               | 75     | XYLENE REACH Reg.: 01-2119488216-32-xxxx                      |
| Point               | 75     | TITANIUM DIOXIDE REACH Reg.: 01-2119489379-17-0018            |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| Flam. Liq. 2      | Flammable liquid, category 2                                       |
| Flam. Liq. 3      | Flammable liquid, category 3                                       |
| Repr. 1B          | Reproductive toxicity, category 1B                                 |
| Acute Tox. 4      | Acute toxicity, category 4                                         |
| Asp. Tox. 1       | Aspiration hazard, category 1                                      |
| STOT RE 2         | Specific target organ toxicity - repeated exposure, category 2     |
| Eye Dam. 1        | Serious eye damage, category 1                                     |
| Skin Irrit. 2     | Skin irritation, category 2                                        |
| STOT SE 3         | Specific target organ toxicity - single exposure, category 3       |
| Skin Sens. 1      | Skin sensitization, category 1                                     |
| Aquatic Acute 1   | Hazardous to the aquatic environment, acute toxicity, category 1   |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225              | Highly flammable liquid and vapour.                                |
| H226              | Flammable liquid and vapour.                                       |
| H360F             | May damage fertility.                                              |
| H302              | Harmful if swallowed.                                              |
| H312              | Harmful in contact with skin.                                      |
| H332              | Harmful if inhaled.                                                |
| H304              | May be fatal if swallowed and enters airways.                      |
| H373              | May cause damage to organs through prolonged or repeated exposure. |

|      |                                                       |
|------|-------------------------------------------------------|
| H318 | Causes serious eye damage.                            |
| H315 | Causes skin irritation.                               |
| H335 | May cause respiratory irritation.                     |
| H317 | May cause an allergic skin reaction.                  |
| H336 | May cause drowsiness or dizziness.                    |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects.    |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148

|                              |                                                                                   |
|------------------------------|-----------------------------------------------------------------------------------|
| <b>COMEC ITALIA SRL</b>      | Revision nr. 4<br>Dated 03/03/2025                                                |
| <b>PLT 7 WHITE 2: 60 BN,</b> | Printed on 03/03/2025<br>Page n. 22/22<br>Replaced revision:3 (Dated: 07/03/2024) |

- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:  
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.  
This document must not be regarded as a guarantee on any specific product property.  
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.  
**CALCULATION METHODS FOR CLASSIFICATION**  
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.  
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.  
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

For information on any exposure scenarios of the substances present in the mixture, contact Sericom Italia srl.

Changes to previous review:  
The following sections were modified:  
03 / 04 / 07 / 08 / 11 / 13 / 14 / 15.